


20
22

 **Beta** *Action*

Promotion
valid until 31/12/2022





























Beta

RSC55



**Configure
your workshop
on-line**

WWW.RSC55.COM

WORKSHOP EQUIPMENT C45PRO - RSC55	2÷4	
CONTAINERS	5÷10	
ASSORTMENT AND THERMOFORMED TRAYS	11÷16	
COMBO - MODULAR SYSTEM	18-19	
WORKBENCHES	20-21	
TROLLEYS AND BASKETS	17-21-22	
TOOL BAGS	23÷26	
WRENCHES	27÷30	
SCREWDRIVERS	31	
COLOR CODE ITEMS	32-33	
SOCKETS	34÷36	
TORQUE WRENCHES	37-38	
PLIERS	39-40	
DRILLING AND THREADING TOOLS	41-42	
HAMMERS AND CHISELS	43	
GENERAL MAINTENANCE TOOLS	44÷49	
LIGHTING	50÷52	
1000V INSULATED TOOLS	53-54	
CUTTING TOOLS	55	
BETA ABRASIVES	56	
ANGLE GRINDERS	57	
AUTOMOTIVE	58÷81	
CHAIN BLOCKS  Robur	82-83	
PNEUMATIC TOOLS	84÷88	
SAFETY FOOTWEAR	89÷96	
WORKWEAR	97÷103	
BETA COLLECTION	104	

C45PRO

WORKSHOP EQUIPMENT COMBINATION C45PRO

//C45PRO

Combination comprising:

- Fixed module with 7 drawers (C45PRO M7)
- Fixed service module (C45PRO MS)
- Mobile roller cab with 7 drawers (C45PRO C7)
- Two-door tool cabinet (C45PRO AS2)
- 3 perforated tool panels (C45PRO PF)
- 3 wall-mounted cabinets (C45PRO PM)
- 3 wall brackets, wide type (C45PRO SL)
- 1 wall bracket, narrow type (C45PRO SS)



// 045000001 C45PRO X

- Worktop made of stainless steel coated MDF (C45PX/3-2,0MT)



// 305 kg

// 045000002 C45PRO W

- Multi-ply wood worktop (C45PW/3-2,0MT)



// 303 kg



//C45PRO A

Combination comprising:

- Fixed module with 7 drawers (C45PRO M7)
- Fixed service module (C45PRO MS)
- Fixed two-door module (C45PRO MA)
- 3 wall-mounted cabinets (C45PRO PM)
- 3 perforated tool panels (C45PRO PF)
- 2 wall brackets, wide type (C45PRO SL)
- 2 wall brackets, narrow type (C45PRO SS)



// 045000003 C45PRO AX

- Worktop made of stainless steel coated MDF (C45PX/3-2,0MT)



// 206 kg

// 045000004 C45PRO AW

- Multi-ply wood worktop (C45PW/3-2,0MT)



// 204 kg



//C45PRO B

Combination comprising:

- Fixed module with 5 drawers (C45PRO M5)
- Fixed two-door module (C45PRO MA)
- Single-door cabinet (C45PRO AS1)
- 2 wall-mounted cabinets (C45PRO PM)
- 2 perforated tool panels (C45PRO PF)
- 2 wall brackets, wide type (C45PRO SL)
- 1 wall bracket, narrow type (C45PRO SS)



// 045000021 C45PRO BX

- Worktop made of coated MDF stainless steel (C45PX/2-1,3MT)

// 191 kg



// 045000022 C45PRO BW

- Multi-ply wood worktop (C45PW/A2-1,3MT)

// 190 kg



//C45PRO D

Combination comprising:

- 1 mobile roller cab with 7 drawers (C45PRO M7)
- 1 mobile roller cab with 7 drawers (C45PRO C7)
- 1 fixed service module (C45PRO MS)
- 1 fixed module with 5 drawers (C45PRO M5)

- 1 fixed module with 2 doors (C45PRO MA)
- 5 perforated tool panels (C45PRO PF)
- 5 wall-mounted cabinets (C45PRO PM)
- 7 wall brackets, wide type (C45PRO SL)
- 2 wall brackets, narrow type (C45PRO SS)
- 2 single-door tool cabinets (C45PRO AS1)



// 045000031 C45PRO DX

- 1 worktop made of stainless steel coated MDF 2,0 m (C45PX/3-2,0MT)
- 1 worktop made of stainless steel coated MDF 1,3 m (C45PX/2-1,3MT)
- 1 self-supporting complete corner with stainless steel coated MDF worktop (C45PRO C/X)



// 572 kg



// 045000032 C45PRO DW

- 1 multi-ply wood worktop 2 m (C45PW/3-2,0MT)
- Multi-ply wood worktop 1,3 m (C45PW/2-1,3MT)
- 1 self-supporting complete corner with wood worktop (C45PRO C/W)



// 568 kg

C55

WORKSHOP EQUIPMENT COMBINATION RSC55

055000065

C55PB-PRO/7



WORKSHOP EQUIPMENT COMBINATION RSC55

Composed of:

C55B

Workbench with worktop (2050x700 mm) covered with a shockproof, nonscratch ABS coat resistant to oils and hydrocarbons.

Fitted with:

- Holes for a vice (1599F/150, to be ordered separately)
- Vertically adjustable feet

C55M7

Fixed module with seven drawers (588x367 mm) with ball bearing slides

- Aluminium opening system throughout length of drawer
- Drawer bases protected by foamed rubber mats
- Front centralized lock
- Can be fitted with thermoformed trays

C55MS

Fixed service module

- Built-in waste bin
- Paper roll compartment
- Storage drawer, 305x270 mm

C55/2PM + C55/PF

Tool wall system with 2 suspended cabinets

- 2 suspended cabinets, 1024x400x300 mm, with gas springs
- 2 under-cabinet panels, 1024x620x25 mm
- 2 under-cabinet perforated tool panels, 1024x620x25 mm



055000066

C55PB-PRO/8



WORKSHOP EQUIPMENT COMBINATION RSC55

Composed of:

C55B

Workbench with worktop (2050x700 mm) covered with a shockproof, nonscratch ABS coat resistant to oils and hydrocarbons.

Fitted with:

- Holes for a vice (1599F/150, to be ordered separately)
- Vertically adjustable feet

C55C7

Mobile roller cab with seven drawers (588x367 mm) with ball bearing slides

- 4 castors Ø 100 mm, 2 fixed and 2 steering (one with brake)
- Aluminium opening system throughout length of drawer
- Drawer bases protected by foamed rubber mats
- Front centralized lock
- Can be fitted with thermoformed trays

C55MA

Fixed two-door module

- Push-pull opening system
- With lock
- Interior shelf, vertically adjustable

C55PS

Tool wall system with shutter and framework

- Aluminium shutter, vertically adjustable, with lock
- Removable perforated tool panel



NEW



//C37A/7

MOBILE ROLLER CAB WITH 7 DRAWERS WITH ANTI-TILT SYSTEM

//C37

MOBILE ROLLER CAB

Main features:

- Sturdy multi-purpose worktop
- Quick release system made of aluminium, opening throughout length of drawer
- Corner bumpers throughout height of roller cab, to avoid damaging vehicles in garage
- Four castors Ø 125 mm: 2 fixed and 2 steering (one with brake)
- Tote-trays and holes for accommodating screwdrivers
- Built-in side bottle and paper holders, adjustable in several positions



1004 mm
482 mm
803 mm

71 kg



n°		Max
5	75 mm	30 kg
1	150 mm	35 kg
1	225 mm	35 kg



	Ral 2011	Ral 7016	Ral 3000	n°	Max	kg
C37/6	037000061	037000062	037000063	4 1 1	75 mm 150 mm 305 mm	30 kg 35 kg 40 kg
C37/7	037000071	037000072	037000073	5 1 1	75 mm 150 mm 225 mm	30 kg 35 kg 35 kg
C37/8	037000081	037000082	037000083	6 2	75 mm 150 mm	30 kg 35 kg

Ral 2011	Ral 7016	Ral 3000
037000271	037000272	037000273


//C39

MOBILE ROLLER CAB


- Four castors with steel cores, Ø 125 mm: 2 fixed and 2 steering (one with brake)
- Front centralized safety lock
- Sturdy multi-purpose worktop with tote-trays and holes for accommodating screwdrivers
- Pull-out drawer with opening system throughout its length
- Built-in side and rear bottle and paper holders



UPRIGHTS AND DRAWER FRONT MADE OF ALUMINIUM ALLOY + STURDINESS + LIGHTWEIGHTNESS



971 mm
500 mm
800 mm



	Ral 2011	Ral 7016	Ral 3000	n°	Max	kg
C39/6	039000031	039000032	039000033	4 1 1	70 mm 140 mm 280 mm	30 kg 35 kg 40 kg
C39/7	039000001	039000002	039000003	5 1 1	70 mm 140 mm 210 mm	30 kg 35 kg 35 kg
C39/8	039000041	039000042	039000043	6 2	70 mm 140 mm	30 kg 35 kg

NEW



DISCOVER THE NEW RSC!

Beta is proud to introduce **the new RSC product range**, designed to meet every professional's requirements and ensure remarkable reliability and high performance.

The new design, inspired by the Racing world, gives this range of cabs and trolleys a charming, unique style: based on the new colours and finishes, the new RSC product range stands out as one of a kind in the market.

The sturdy structure and the materials used guarantee high quality and a long service life, thus effectively complementing the daily work of industrial production departments, vehicle repairers and general maintainers. Furthermore, most of the RSC mobile roller cabs have been awarded prestigious TÜV certification, which is synonymous with guaranteed safety and quality, and is obtained upon successful completion of severe tests under the EK5/TA5 protocol.



ACCESSORIES

024004901 2400 RSC24/PL

Wood worktop
for roller cab RSC24



024004902 2400 RSC24/PF

Perforated tool panel with supports,
for roller cab RSC24



024004909 2400 RSC24/SPC

Computer bracket
for mobile
roller cab RSC24

- With removable drawer
- Cannot be used with model RSC24AXL




NEW

050000901 5000MS

Folding shelf

- For use as additional worktop
- Worktop dimensions: 390x440 mm, protected by an anti-oil and anti-petrol rubber mat
- Load capacity: 20 kg.



2400 RSC24/PD

Document holder,
for roller cabs RSC24



2400 RSC24/PC

Paper roll holder



ANTHRACITE	024004907	
BLACK	024004908	

ANTHRACITE	024004903	
BLACK	024004904	

//RSC24

MOBILE ROLLER CAB


- Multi-purpose top with anti-fall edges and eight holes for accommodating screwdrivers
- Drawer bases protected by foamed rubber mats
- Four castors Ø 125 mm: 2 fixed and 2 steering (one with brake)
- Each drawer can accommodate up to 4 EVA foam or ABS thermoformed trays
- Front centralized safety lock.
- Static load capacity: 800 kg.
- Built-in bottle holder (can be applied on both sides).

The following accessories can be added:

- wood worktop 2400 RSC24/PL
- perforated tool panel 2400 RSC24/PF
- folding shelf 5000MS
- document holder 2400 RSC24//PD
- paper roll holder 2400 RSC24/PC



NEW



	Ral 2011	Ral 7016	Ral 5015 Ral 7016	Ral 9006 Ral 7016	Ral 9005	Ral 2011 Ral 7016	Ral 3000 Ral 7016	kg	
RSC24/5	024004050	024004057	024004056	024004052	024004059	024004051	024004053	60	
RSC24/6	024004060	024004067	024004066	024004062	024004069	024004061	024004063	62	
RSC24/7	024004070	024004077	024004076	024004072	024004079	024004071	024004073	63	
RSC24/8	024004080	024004087	024004086	024004082	024004089	024004081	024004083	66	

RSC24/5		
n°		Max
2	70 mm	25 kg
2	140 mm	30 kg
1	280 mm	35 kg

RSC24/6		
n°		Max
4	70 mm	25 kg
1	140 mm	30 kg
1	280 mm	35 kg

RSC24/7		
n°		Max
5	70 mm	25 kg
1	140 mm	30 kg
1	210 mm	30 kg

RSC24/8		
n°		Max
6	70 mm	25 kg
2	140 mm	30 kg

RSC24AXL

MOBILE ROLLER CAB, WITH ANTI-TILT SYSTEM, LONG MODEL

- New ABS reinforced worktop with anti-fall edges, eight holes for accommodating screwdrivers and 6 tote trays.
- **Sturdy nylon front, with built-in label holder.**
- Drawer bases protected by foamed rubber mats.
- 4 castors, Ø 125 mm: 2 fixed and 2 steering (one with brake).
- Front centralized safety lock.
- Built-in side bottle holder (can be applied on both sides).


Following accessories can be added:

- Wood worktop 2400 RSC24/PL
- Document holder 2400 RSC24/PD-A
- Paper roll holder 2400 RSC24/PC-A

1000



970 mm
445 mm
1035 mm



	Ral 2011 Ral 7016	Ral 7016	Ral 3000 Ral 7016	n°	↓ max	kg	
RSC24AXL/7	024004271	024004277	024004273	5	70 mm	30 kg	84
				1	140 mm	35 kg	
				1	210 mm	35 kg	
RSC24AXL/8	024004281	024004287	024004283	6	70 mm	30 kg	88
				2	140 mm	35 kg	
RSC24AXL/9	024004291	024004297	024004293	8	70 mm	30 kg	90
				1	140 mm	35 kg	

RSC24L/7

MOBILE ROLLER CAB WITH 7 DRAWERS AND SIDE SHELVES

Main features:


- 7 drawers (588x367 mm) with ball bearing slides:
 - 5 drawers, 70 mm high
 - 1 drawer, 140 mm high
 - 1 drawer, 210 mm high.
- Drawer bases protected by foamed rubber mats.
- 4 castors, Ø 125 mm: 2 fixed and 2 steering with brakes.
- Front centralized lock.
- Static load capacity: 1,100 kg.
- Multi-ply wood worktop with holes for a vice (1599F/100, to be ordered separately).
- Side compartment with vertically adjustable shelf.
- Built-in paper roll holder.
- Double rear bottle holder.

1100



973 mm
565 mm
1050 mm

80 kg



Ral 2011 Ral 7016	Ral 7016	Ral 3000 Ral 7016	n°	↓ Max	kg
024004371	024004377	024004373	5	70 mm	25 kg
			1	140 mm	30 kg
			1	210 mm	30 kg



RSC24L-CAB

MOBILE ROLLER CAB WITH 7 DRAWERS AND TOOL CABINET

Main features:

- 7 drawers (588x367 mm) with ball bearing slides: 5 drawers, 70 mm high, 1 drawer, 140 mm high, 1 drawer, 210 mm high.
- Drawer bases protected by foamed rubber mats.
- 4 castors, Ø 125 mm: 2 fixed and 2 steering with brakes.
- Front centralized lock.
- Side tool cabinet with lockable door and vertically adjustable interior shelf.
- Static load capacity: 1,100 kg.
- Multi-ply wood worktop with holes for a vice (1599F/100, to be ordered separately).
- Built-in paper roll holder.
- Double rear bottle holder.



1100 kg




973 mm
565 mm
1050 mm



Ral 2011	Ral 7016	Ral 3000
Ral 7016	Ral 7016	Ral 7016
024004471	024004477	024004473

n°	mm	Max
5	70 mm	25 kg
1	140 mm	30 kg
1	210 mm	30 kg

82 kg



RSC28

SUPERTANK TROLLEY WITH WOOD WORKTOP AND 10 DRAWERS

Main features:

- 10 drawers (588x367 mm) with ball bearing slides.
- Quick, safe system for opening and closing drawers, with nylon and fibreglass front.
- 5 side drawers: 4 drawers, 70 mm high, 1 drawer, 210 mm high.
- 5 front drawers: 4 drawers, 70 mm high, 1 drawer, 210 mm high.
- Drawer bases protected by foamed rubber mats.
- 4 high-capacity castors, Ø 150 mm: 2 fixed and 2 steering with brakes.
- 2 centralized safety locks.
- 3 front tool drawers.
- Multi-ply wood worktop with holes for a vice (1599F/150, to be ordered separately).
- Built-in tool compartment.
- Side compartment with foldaway door with lock.
- Built-in bottle holders.
- 135-mm-high storage compartment with plastic-covered base.

1200 kg




943 mm
800 mm
1235 mm

130 kg



Ral 2011	Ral 7016	Ral 3000
Ral 7016	Ral 7016	Ral 7016
028003001	028003007	028003003

n°	mm	Max
8	70 mm	25 kg
2	210 mm	30 kg



//C50S

SERVICE TOOL TROLLEY WITH 3 DRAWERS

Main features:

- Thermoplastic worktop
- 3 drawers (588x367 mm) with ball bearing slides, 70 mm high
- Drawer bases protected by foamed rubber mats
- Front centralized safety lock
- Large lower shelf protected by an anti-oil and anti-rubber mat
- Four castors, Ø 125 mm: 2 fixed and 2 steering (one with brake)
- Static load capacity: 400 kg
- Capacity of each drawer: 15 kg, uniformly distributed
- Paper roll holder item 2400S-R/PC can be applied on request
- **Folding shelf item 5000MS can be applied on request**

kg
400



- Convenient side screwdriver holder included
- Two side built-in spray can holders

890 mm
460 mm
770 mm



Ral 2011	Ral 7016	Ral 3000
050000301	050000302	050000303

38 kg




n°	mm	Max
3	70 mm	15 kg



050000901 **5000MS**

Folding shelf for tool trolley item C50S RSC24-RSC24A



024003077 **C04TSS/7**

MOBILE ROLLER CAB WITH 7 DRAWERS

made of stainless steel

- Four castors with steel cores, Ø 125 mm: 2 fixed and 2 steering (with brakes);
- Front centralized lock;
- Frame made entirely of stainless steel
- Castors, supports, ball bearings, drawer interiors and guides made of stainless steel
- Drawer handles made of aluminium



kg
700



935 mm
470 mm
680 mm

63 kg

n°	mm	max
6	83 mm	25 kg
1	170 mm	30 kg



Non-marking wheels






059880356 5988VU/M




ASSORTMENT OF 214 TOOLS IN SOFT FOAM TRAY

Recommended with: RSC24 -RSC24L/7 - C37 - C39 - RSC28 - RSC24L-CAB C59 - RSC55


Quantity/Description	Beta N.	TR
22 combination wrenches 6-7-8-9-10-11-12-13-14-15-16-17-18-19-20-21-22-24-27-30-32-36 mm	42	M01
11 double open end wrenches 6x7-8x9-10x11-12x13-14x15-16x17-18x19-20x22-21x23-24x27-30x32 mm	55	M30
11 double ended offset ring wrenches 6x7-8x9-10x11-12x13-14x15-16x17-18x19-20x22-21x23-24x27-30x32 mm	90	M30
9 ball head offset hexagon key wrenches \odot 1,5+10 mm	96BPC/SC9	M30
1 socket holder	895/1	M100
1 socket holder	895/3	M100
1 socket holder	895/6	M100
13 1/4" hexagon sockets \odot 4-4,5-5-5,5-6-7-8-9-10-11-12-13-14 mm	900	M100
9 hexagon hand sockets, long series \odot 5-6-7-8-9-10-11-12-13 mm	900L	M100
5 1/4" socket drivers for hexagon screws \odot 3-4-5-6-7 mm	900ME	M100
4 socket drivers for slotted head screws \bullet 0,8x4-1x5,5-1,2x6,5-1,2x8 mm	900LP	M100
4 socket drivers for cross head Phillips® screws \bullet PH1-PH2-PH3-PH4	900PH	M100
7 socket drivers for Torx® head screws \odot T10-T15-T20-T25-T27-T30-T40	900TX	M100
1 1/4" drive extension bar 50 mm	900/20	M100
1 1/4" drive extension bar 100 mm	900/20L	M100
1 1/4" drive extension bar 150 mm	900/21	M100
1 1/4" drive universal joint	900/25	M100
1 1/4" drive spinner handle	900BG/30	M100
1 1/4" drive swivel T-handle	900/42	M100
1 1/4" reversible ratchet \oplus	900/55	M100
21 1/2" square drive hexagon sockets \odot 8-10-11-12-13-14-15-16-17-18-19-20-21-22-23-24-26-27-28-30-32 mm	920A	M100
1 adaptor, 1/2" female and 3/8" male drives 125 mm	920/15	M100
1 1/2" drive universal joint 250 mm	920/25	M100
1 1/2" wobble extension bar 125 mm	920AN/125	M100
1 1/2" wobble extension bar 250 mm	920AN/250	M100
1 1/2" drive sliding T-handle 305 mm	920/42	M100
1 1/2" drive reversible ratchet \oplus	920/55	M100
8 1/2" sockets for Torx® head screws \odot 10-12-14-16-18-20-22-24 mm	920FTX	M100
11 hexagon hand sockets \odot 10-12-13-14-15-16-17-18-19-21-22 mm	920AL	M100
1 circlip pliers straight, internal \odot 180 mm	1032	M129
1 circlip pliers bent, internal \odot 170 mm	1034	M129
1 circlip pliers straight, external \bullet 175 mm	1036	M129
1 circlip pliers bent, external \bullet 175 mm	1038	M129
1 circlip pliers bent, external \bullet 175 mm	1048	M129
1 self - locking pliers 240 mm	1052	M129
1 Diagonal cutting nippers \nless 160 mm	1082BM	M129
1 construction worker's pincers 220 mm	1098	M129
1 tin snips 250 mm	1112	M129
1 electrician's scissors, straight blades	1128BM	M129
1 half-round needle nose pliers \equiv 180 mm	1150BM	M129
1 Extra-long needle nose pliers \bullet 160 mm	1166BM	M129
1 Extra-long bent needle nose pliers \bullet 160 mm	1168BM	M129
6 screwdriver for slotted head screws \bullet 2,5x50-3x75-4x100-5,5x125-6,5x150-8x200 mm	1201E	M213



M01



M30



25



25




M123



M230



M129



M100

- | | | |
|---|-------------|------|
| 1 screwdriver for slotted head screws, extra-short series \bullet 4x30 mm | 1201EN | M213 |
| 4 screwdriver for cross head Phillips® screws \bullet PH0,60-PH1x80-PH2x100-PH3x150 mm | 1202E | M213 |
| 1 screwdriver for cross head Phillips® screws, extra-short series \bullet PH1x30 mm | 1202EN | M213 |
| 12 screwdrivers for Torx® head screws, with handles \odot T6-T7-T8-T9-T10-T15-T20-T25-T27-T30-T40-T45 | 1207E/TX | M213 |
| 1 mains testing screwdriver \bullet | 1253 | M213 |
| 3 drift punches 2-3-4 mm | 30 | M230 |
| 1 pin punches 2-3-4-5-6-8 | 31 | M230 |
| 1 centre punch \varnothing 4 mm | 32 | M230 |
| 1 flat chisels 150 mm | 34 | M230 |
| 2 flat chisels, ribbed type 200-250 mm | 35 | M230 |
| 1 cape chisels, standard type 125 mm | 36 | M230 |
| 1 engineer's hammer 500 g | 1370 | M230 |
| 1 soft face hammer \varnothing 35 mm | 1390 | M230 |
| 1 measuring tape 3 m | 1692 | M230 |
| 1 telescopic magnet with flexible head | 1712TF | M230 |
| 1 second-cut square files 200 mm | 1719BMA...Q | M230 |
| 1 second-cut triangular files 200 mm | 1719BMA...T | M230 |
| 1 second-cut flat files 200 mm | 1719BMA...P | M230 |
| 1 second-cut half-round files 200 mm | 1719BMA...M | M230 |
| 1 second-cut round files 200 mm | 1719BMA...R | M230 |
| 1 steel wire brush | 1737NX | M230 |
| 1 snap - off blade utility knife 18 mm | 1771 | M230 |




059040416 5904VA/T



ASSORTMENT OF 102 TOOLS IN ABS


Quantity/Description	Beta N.	TR
21 combination wrenches 6-7-8-9-10-11-12-13-14-15-16-17-18-19-20-21-22-24-27-30-32 mm	42	T05
8 double open end wrenches 6x7-8x9-10x11-12x13-14x15-16x17-18x19-20x22 mm	55	+T06 T33
9 offset hexagon key wrenches \odot 1,5+10 mm	96/SC9	T33
6 offset hexagon key wrenches \odot 2-2,5-3-4-5-6 mm	96T	T52
8 T - handle wrenches with swivelling socket \odot 7-8-10-12-13-14-17-19 mm	952	T63
19 1/2" square drive hexagon sockets \odot 10-11-12-13-14-15-16-17-18-19-20-21-22-23-24-26-27-30-32 mm	920A	T83
1 1/2" drive extension bar 125 mm	920/21	T83
1 1/2" drive extension bar 255 mm	920/22	T83
1 1/2" drive universal joint	920/25	T83
1 1/2" drive sliding T-handle 305 mm	920/42	T83
1 1/2" drive reversible ratchet \oplus	920/55	T83
1 heavy-duty diagonal cutting nippers \nless 160 mm	1084BM	T137
1 half-round needle nose pliers \equiv 180 mm	1150BM	T137
1 extra-long needle nose pliers \bullet 160 mm	1166BM	T137
1 circlip pliers straight, internal \odot 180 mm	1032	T145
1 circlip pliers bent, internal \odot 170 mm	1034	T145
1 circlip pliers straight, external \bullet 175 mm	1036	T145
1 circlip pliers bent, external \bullet 175 mm	1038	T145
1 self - locking pliers 240 mm	1052	T153
1 slip joint pliers boxed joints 250 mm	1048	T153
7 screwdrivers for cross head Phillips® screws \bullet 2,5x50 -3x75 - 3,5x100 - 4x125 -5,5x100 - 5,5x150 - 6,5x150 mm	1260	T199
6 screwdrivers for cross head Phillips® screws \oplus PH0x60 - PH0x100 - PH1x80 - PH1x120 - PH2x100 - PH2x150 mm	1262	T202
2 flat chisels, ribbed type 100-200 mm	35	T234
1 engineer's hammer 300 g	1370	T234
1 soft face hammer \varnothing 35 mm	1390	T234
1 empty thermoformed tray		VP5



T199 T202 T83



T145 T153 T137 T234



T52 T33 T05 T06



T63 VP5



059040426

5904VU/M

SOFT
MODULE
SYSTEM

ASSORTMENT OF 91 TOOLS IN SOFT FOAM TRAY

Recommended with: RSC24 - RSC24L/7 - C37 - C39
RSC28 - RSC24L-CAB - C59 - RSC55

16

17

7

6



M05

M33

M199

M202

8

24



M50

M83

3

2

4

4



M137

M153

M234

M145

Quantity/Description

	Beta N.	TR
16 combination wrenches 6÷21 mm	42	M05
8 double open end wrenches 6x7 - 8x9 - 10x11 - 12x13 - 14x15 - 16x17 - 18x19 - 20x22 mm	55	M33
9 offset hexagon key wrenches \odot 1,5 - 2 - 2,5 - 3 - 4 - 5 - 6 - 8 - 10 mm	96/SC9	M33
7 screwdrivers for cross head Phillips® screws \bullet 2,5x50 - 3x75 - 3,5x100 - 4x125 - 5,5x100 - 5,5x150 - 6,5x150 mm	1260	M199
6 screwdrivers for cross head Phillips® screws \oplus PH0x60 - PH0x100 - PH1x80 - PH1x120 - PH2x100 - PH2x150 mm	1262	M202
8 offset hexagon key wrenches \odot 2-2,5-3-4-5-6-7-8 mm	96T	M50
1 1/2" wobble extension bar 125 mm	920AN/125	M83
1 1/2" wobble extension bar 250 mm	920AN/250	M83
1 1/2" drive universal joint	920/25	M83
1 1/2" drive sliding T-handle	920/42	M83
1 1/2" drive reversible ratchet \oplus	920/55	M83
19 1/2" square drive hexagon sockets \odot 10÷24 - 26 - 27 - 30 - 32 mm	920A	M83
1 Heavy-duty diagonal cutting nippers \nless 160 mm	1084	M132
1 half-round needle nose pliers \equiv 180 mm	1150	M132
1 extra-long needle nose pliers \bullet 160 mm	1166	M132
1 slip joint pliers boxed joints 250 mm	1048	M153
1 self - locking pliers 240 mm	1052	M153
2 flat chisels, ribbed type 100-200 mm	35	M234
1 engineer's hammer 300 g	1370	M234
1 soft face hammer \varnothing 35 mm	1390	M234
1 circlip pliers straight, internal \odot 180 mm	1032	M145
1 circlip pliers bent, internal \odot 170 mm	1034	M145
1 circlip pliers straight, external \bullet 175 mm	1036	M145
1 circlip pliers bent, external \bullet 175 mm	1038	M145



059041220

5904VG/3M

SOFT
MODULE
SYSTEM

ASSORTMENT OF 130 TOOLS IN SOFT FOAM TRAY

Recommended with: RSC24 - RSC24L/7 - C37 - C39 - RSC28 - RSC24L - CAB - C59 - RSC55



16


5

2

8

5


4



M05

M06

M153



M50

M55

M292

10

45

4

24

3


4



M208

M85

M234



M83


M134

M145

Quantity/Description

	Beta N.	TR
16 combination wrenches 6÷21 mm	42	M05
5 combination wrenches 22 - 24 - 27 - 30 - 32 mm	42	M06
1 slip joint pliers boxed joints 250 mm	1048	M153
1 self - locking pliers 240 mm	1052	M153
8 offset hexagon key wrenches \odot 2-2,5-3-4-5-6-7-8 mm	96T	M50
5 drivers for Torx® head screws, with handles \odot T10-T15-T20-T25-T30	97TTX	M55
1 adjustable wrench 250 mm	111	M292
1 electrician's scissors, straight blades	1128BMX	M292
1 measuring tape 5 m	1692/5	M292
1 snap - off blade utility knife 170 mm	1771	M292
5 screwdrivers for cross head Phillips® screws \bullet 3x75 - 3,5x100 - 4x125 - 5,5x150 - 6,5x150 mm	1260	M208
3 screwdrivers for cross head Phillips® screws \oplus PH0x60 - PH1x80 - PH2x100 mm	1262	M208
1 screwdrivers for slotted head screws, extra-short series \bullet 4x30 mm	1260N	M208
1 screwdrivers for cross head Phillips® screws, extra - short series \oplus PH1x30 mm	1262N	M208
5 bits for slotted head screws, coloured \bullet 0,5x3 - 0,6x4,5 - 0,8x5,5 - 1x5,5 - 1,2x6,5 mm	860LP	M85
8 hexagon bits for power drivers, coloured \odot 2 - 2,5 - 3 - 4 - 5 - 6 - 8 - 10 mm	860PE	M85
5 bits for cross head Phillips® screws, coloured \oplus PH0 - PH1 - PH2 - PH3 - PH4	860PH	M85
4 bits for cross head Pozidriv® - Supadriv® screws, coloured	860PZ	M85
11 bits for Torx® head screws, coloured \odot T6-T7-T8-T9-T10-T15-T20-T25-T27-T30-T40	860TX	M85
8 bits for Tamper Resistant Torx® head screws, coloured \oplus T9-T10-T15-T20-T25-T27-T30-T40	860RTX	M85
1 magnetic bit holder with handle 230 mm	851SR	M85
1 reversible bit ratchet 100 mm	860/55	M85
1 magnetic bit holder extension bar 80 mm	882P	M85
1 adaptors for drivers \blacksquare 1/4 - \square 1/4	892	M85
2 flat chisels, ribbed type 100 - 200 mm	35	M234
1 engineer's hammer 300 g	1370	M234
1 soft face hammer \varnothing 35 mm	1390	M234
1 1/2" wobble extension bar 125 mm	920AN	M83
1 1/2" wobble extension bar 250 mm	920AN	M83
1 1/2" drive universal joint	920/25	M83
1 1/2" drive sliding T-handle	920/42	M83
1 1/2" drive reversible ratchet \oplus	920/55	M83
19 1/2" square drive hexagon sockets \odot 10÷24-26-27-30-32 mm	920A	M83
1 diagonal cutting nippers \nless 160 mm	1082GBM	M134
1 combination pliers \equiv 180 mm	1150GBM	M134
1 extra long needle knurled nose pliers \bullet 160 mm	1166GBM	M134
1 circlip pliers straight, internal \odot 180 mm	1032	M145
1 circlip pliers bent, internal \odot 170 mm	1034	M145
1 circlip pliers straight, external \bullet 175 mm	1036	M145
1 circlip pliers bent, external \bullet 175 mm	1038	M145

024500001 M01



42 6-7-8-9-10-11-12-13-14-15-16-17-18
19-20-21-22-24-27-30-32-36 mm

4,5 kg

024500030 M30



55 6x7-8x9-10x11-12x13-14x15-16x17-18x19-20x22-21x23-24x27-30x32 mm
90 6x7-8x9-10x11-12x13-14x15-16x17-18x19-20x22-21x23-24x27-30x32 mm
96BPC/SC9 1,5-2-2,5-3-4-5-6-8-10 mm

4,2 kg

024500044 M44



141 8-9-10-11-12
13-14-15-16
17-18-19 mm

1,3 kg

024500060 M60



96T 2-2,5-3-4-5-6-7-8-10 mm
97BTX/SC8 T9-T10-T15-T20-T25-T27-T30-T40 mm
944BX 5-6-7-8-10-13 mm

1,9 kg




024500063 M63



952 7-8-10-12-13-14-17-19 mm

3,4 kg

024500100 M100 1/4" 1/2"



6,7 kg

895/1 - 895/3 - 895/6
900 4-4,5-5-5,5-6-7-8-9-10-
11-12-13-14 mm
900L 5-6-7-8-9-10-11-12-13 mm
900ME 3-4-5-6-7 mm
900LP 0,8x4-1x5,5-1,2x6,5-1,2x8 mm
900PH PH1-PH2-PH3-PH4
900TX T10-T15-T20-T25-T27-T30-T40
900/20 50 mm - 900/20L 100 mm
900/21 150 mm
900/25 - 900BG/30 - 900/42

900/55
920A 8-10-11-12-13-14-15-16-17-
18-19-20-21-22-23-24-26-27-
28-30-32 mm
920/15 - 920/25
920AN/125 125 mm
920AN/250 250 mm
920/42
920/55
920FTX 10-12-14-16-18-20-22-24 mm
920AL 10-12-13-14-15-16-17-18-
19-21-22 mm

024500871 M105 14" 38" 12"



7,7 kg

- 900 4-4,5-5,5-6-7-8-9-10
11-12-13-14 mm
- 900L 5-6-7-8-9-10-11-12-13 mm
- 96BPC/SC9 1,5-2-2,5-3-4-5-6-8-10 mm
895/1 - 895/3 - 895/6
- 900ME 3-4-5-6-7 mm
- 900LP 0,8x4-1x5,5-1,2x6,5-2x8 mm
- 900PH PH1-PH2-PH3-PH4
- 900TX T10-T15-T20-T25-T27-T30-T40
- 900/16 □ 1/4 - ■ 3/8
- 900/... 50-100-150 mm
- 900/25 - 900BG/30 - 900/42
- 900/55
- 910A 6-7-8-9-10-11-12-13-14-15-16-
17-18-19-20-21-22 mm
- 910/15 □ 3/8 - ■ 1/4
- 910/16 □ 3/8 - ■ 1/2
- 910/21 125 mm
- 910/22 250 mm
- 910/25 - 910/42
- 910/55
- 920A 8-10-11-12-13-14-15-16-17
18-19-20-21-22-23-24-26
27-28-30-32 mm
- 1/2 - ■ 3/8
- 920/15
- 920/25
- 920AN 125 - 250 mm
- 920/42
- 920/55
- 956E 16-17,8-20,8 mm

024500115 M115 12"



7,8 kg

- 666N 40÷200 Nm
- 920A 13-14-15-16-17-18-19-20-21-22-24-
26-27-30-32 mm
- 920FTX 12-14-16-18-20-22-24 mm
- 920PE 6-7-8-8L-10-10L-12-12L-14-14L
- 920TX T20-T25-T27-T30-T40-T45-T50-
T55-T60-T20L-T25L-T27L-T30L-
T40L-T45L-T50L
- 920/21 125 mm
- 920/22 255 mm
- 920/25
- 920/42 305 mm
- 920/55

024500120 M120 12"



6,9 kg

- 920A 10-11-12-13-14-15-16-17-18-
19-20-21-22-24-26-27-30-32 mm
- 920AN/125 125 mm
- 920AN/250 250 mm
- 920/25 - 920/42
- 920AL 10-12-13-14-15-16-17-18-19-22-24-27-30-32 mm
- 920FTX 10-12-14-16-18-20-22-24 mm
- 920/55
- 920PE 5-5L-6-6L-7-7L-8-8L-10-10L-12-12L-14-14L
- 920TX T20-T25-T27-T30-T40-T45-T50-T55-T60-
T20L-T25L-T27L-T30L-T40L-T45L-T50L

024500128 M128 12"



8,9 kg

- 720 10-11-12-13-14-15-16-17-18-19-21-22-24-27-30-32 mm
- 720L 11-12-13-14-15-16-17-18-19-21-22-24-27-30-32 mm
- 720TX T30-T40-T45-T50-T55
- 720ME 5-6-8-10-12-14-17-19 mm
- 720LC 17-19-21 mm
- 720/21 125 mm
- 720/25

024500129 M129



13

- 1032 180 mm
- 1034 170 mm
- 1036 175 mm
- 1038 175 mm
- 1048 250 mm
- 1052 240 mm
- 1082BM 160 mm
- 1098 220 mm
- 1112 250 mm
- 1128BM
- 1150BM 180 mm
- 1166BM 160 mm
- 1168BM 160 mm

3,4 kg

024500133 M133



3

- 1082G 160 mm
- 1150G 180 mm
- 1166G 160 mm

650 g

024500134 M134



3

- 1082GBM 160 mm
- 1150GBM 180 mm
- 1166GBM 160 mm

750 g


024500162 M162



024500195 M195



024500213 M213



024500230 M230



024240001 T01



024240005 T05



024240006 T06



024240031 T31



024240040 T40



024240045 T45



024240050 T50



024240055 T55





024240063 **T63**

8

952 7-8-10-12-13-14-17-19 mm

3,8 kg



024240083 **T83**

24

12"

920A 10-11-12-13-14-15-16-17-18
19-20-21-22-23-24-26-27-30-32 mm
920/21 125 mm 920/42 305 mm
920/22 255 mm 920/55 275 mm
920/25

3,6 kg



024240091 **T91**

25

14"

900 4-4,5-5-5,5-6-7-8-9-10-11-12
13-14 mm
900ME 2,5-3-4-5-6-8 mm
900/20 50 mm
900/21 150 mm
900/25

560 g



024240092 **T92**

22

38"

910A 6-7-8-9-10-11-12-13-14-15-16
17-18-19-20-21-22 mm
910/21 125 mm 910/42 210 mm
910/22 250 mm 910/55 200 mm
910/25

1,5 kg



024240124 **T124**

3

1082GBM 160 mm
1150GBM 180 mm
1166GBM 160 mm

640 g

NEW




024240137 **T137**

3

1084BM 160 mm
1150BM 180 mm
1166BM 160 mm

750 g



024240145 **T145**

4

1032 180 mm
1034 170 mm
1036 175 mm
1038 175 mm

640 g



024240153 **T153**

2

1048 250 mm
1052 240 mm

1,1 kg



024240199 **T199**

7

1260 2,5x50 - 3x75 - 3,5x100
4x125 - 5,5x100 - 5,5x150 -
6,5x150 mm

490 g



024240202 **T202**

6

1262 PH0x60 - PH0x100 - PH1x80
PH1x120 - PH2x100 - PH2x150 mm

490 g



024240205 **T205**

7

1267TX T6-T7-T8-T9-T10-T15-T20

460 g



024240211 **T211**

7

1201E 2,5x50-3x75-3,5x100
4x125-5,5x100-5,5x150-6,5x150 mm

490 g



024240213 **T213**

6

1202E PH0x60-PH1x80
PH1x120-PH2x100
PH2x150-PH3x150 mm

490 g



024240234 **T234**

4

35 100-200 mm
1370 300 g
1390 35 mm

1,3 kg



024240236 **T236**

5

1719BMA/Q 200 mm
1719BMA/T 200 mm
1719BMA/P 200 mm
1719BMA/M 200 mm
1719BMA/R 200 mm

870 g



024240239 **T239**

7

31BM 2-3-4-5-6-8 mm
32 4 mm

850 g

NEW Beta BRUTUS

Beta

048000230 C48M



Electric platform cart, with panels

- Motorized platform, with 24V - 400W motor with 2x12V 33Ah battery supply and Curtis control card.
- Loading floor made from sturdy steel, coated with non-slip rubber, with round tubular panels preventing objects from falling during transport.
- The panels can be removed, to cater to individual transportation requirements.
- Fitted with 2 pneumatic traction wheels (Ø 260 mm) and 2 swivelling rubber wheels (Ø 150mm), electromagnetic brake and differential gear.
- Supplied with an external battery charger, 220V/50Hz - V/A 24/12e.



The control console is equipped with the following:

- ① ignition key
- ② speed adjusting knob
- ③ side butterfly handles for traction control
- ④ intermittent beep, which is activated when moving in reverse
- ⑤ battery charge indicator
- ⑥ electric brake cut-out button
- ⑦ emergency mushroom head button.

**GO AROUND AS LONG AS YOU LIKE!
UP TO 4 HOURS BATTERY LIFE**



**SPEED ADJUSTABLE
FROM 4 TO 6 KM/H**

FUNCTIONAL SPECIFICATIONS

- Carrying capacity: **400 kg**
- Driving speed: **4-6 km/h** (adjustable)
- Battery life: **4 hours**
- Maximum permitted slope with a full load: **6%**
- Maximum permitted slope with 100 kg load: **18%**

SAFETY DEVICES:

- Electronic brake
- Buzzer
- Anti-crushing guard
- Battery charge indicator
- Curtis control cart

TECHNICAL SPECIFICATIONS

- Overall dimensions: 1280x630x1100h mm
- Useful dimensions of loading platform with panels: 1180x580 mm
- Useful dimensions of loading platform without panels: 1260x620 mm
- Height of loading platform from floor: 320 mm
- Height of battery compartment from floor: 65 mm
- Weight with batteries: 140 kg

048000030 C48P

Folding tool trolley

- Loading platform made of reinforced polypropylene (PP), with non-slip coating and TPV inserts for corner protection
- Retractable handle for quick, compact storage
- Four non-marking castors, Ø 125 mm: 2 fixed and 2 steering with brakes
- Maximum capacity: 300 kg.
- Loading platform working width: 705 mm
- Loading platform depth: 480 mm
- Loading platform height: 200 mm



kg
300



kg
11





059900001 **5990V1**

**SOFT
MODULE
SYSTEM**

ASSORTMENT OF 44 TOOLS FOR TOOL CASE COMBO C99V1, in EVA foam tray

Quantity/Description

Beta N.

9	ball head offset hexagon key wrenches Ø 1,5-2-2,5-3-4-5-6-8-10 mm	96BPC/SC9
1	snap - off blade utility knife 18 mm	1771
1	Slip joint pliers boxed joints 250 mm	1048
6	2 drift punches, 1 centre punch, 3 flat chisels with metal holder	38/B6
3	screwdrivers for slotted head screws ● 3,5x100-5,5x125-6,5x150 mm	1260
3	screwdrivers for cross head Phillips® screws ● PH0x60-PH1x80-PH2x100 mm	1262
1	electrician's scissors, straight blades	1128BMX
16	combination wrenches 6-7-8-9-10-11-12-13-14-15- 16-17-18-19-21-22 mm	42NEW
1	measuring tape 5 mt	1692/5
1	engineer's hammer 300 g	1370
1	Diagonal cutting nippers, bi-material handles, industrial finish 160 mm	1082GBM
1	heavy duty combination pliers, bi-material handles, industrial finish 180 mm	1150GBM

**SOFT
MODULE
SYSTEM**



059900003 **5990V3** 14" 12"

ASSORTMENT OF 116 TOOLS FOR TOOL CASE COMBO C99V3/2C, in EVA foam tray

Quantity/Description

Beta N.

5	offset hexagon key wrenches Ø 2,5-3-4-5-6 mm	96T/S5P
1	adjustable wrench 250 mm	111
1	1/4" drive spinner handle	900BG/30
1	mains testing screwdriver ●	1253
1	Pocket spirit level with magnetic V-shaped	1695XS
1	LED inspection torch, made of sturdy anodized aluminium	1833XS/2
31	bits with magnetic quick release bit holder in plastic case ● ○ ⊕ ⊕ ⊕ ⊕	860MIX/A31
1	socket holder	895
12	1/4" hexagon sockets ○ 4-4,5-5-5,5-6-7-8-9-10- 11-12-13 mm	900
1	1/4" drive extension bar 50 mm	900/20
1	1/4" drive extension bar 100 mm	900/20L
1	1/4" drive swivel T-handle	900/42
1	1/4" drive reversible ratchet, 72 tooth mechanism Ⓢ	900/55Z
38	microscrewdriver with 36 interchangeable 4-mm bits and magnetic extension	1256/C36-2
1	soft face hammer Ø 35mm	1390
1	1/4" drive universal joint	900/25
13	1/2" square drive hexagon sockets ○ 10-11-12-13- 14-15-16-17-18-19-20-21-22 mm	920A
1	1/2" drive extension bar 125 mm	920/21
1	1/2" drive extension bar 255 mm	920/22
1	1/2" drive universal joint	920/25
1	1/2" drive sliding T-handle	920/42
1	1/2" drive reversible ratchet Ⓢ	920/55

*Assortment recommended
in combination with C99V3/2C*

COMBO
*Assortment
recommended
in combination
with Beta
Combo C99*

38/B6N

44

*Assortment recommended
in combination with C99V1*

116

NEW

COMBO

COMBO IS BETA'S MODULAR SYSTEM

The tool cases can be easily joined to each other by a simple click, through the functional side snap-on mechanism. The tool cases can be combined as you like, depending on your requirements.

COMBO ABS tool case, with transparent cover

Main features:

- Transparent cover made from sturdy polycarbonate for quick identification of contents
- Interior dimensions: 378x313x61 mm
- Can be padlocked

099000202 C99V0

445x358x118 mm



099000200 C99V0-P12

- Particularly suitable for carrying smallwares, including screws, nuts, washers, rivets and dowels
- Supplied complete with kit of 18 tote trays:
 - 2 red trays, 52x52 mm
 - 3 yellow trays, 104x52 mm
 - 2 blue trays, 104x104 mm
 - 1 green tray, 104x156 mm
 - 2 orange trays, 208x52 mm
 - 2 grey trays, 312x71 mm, and 6 adjustable partitions



kg 25

3,2 kg

445x358x118 mm



2,5 kg

NEW

099000010 C99

BETA COMBO comprehensive modular system

System comprising:

- Aluminium folding tool trolley with telescopic handle C99P (485x520x1195 mm)
- ABS wall tool case C99V1 (445x358x152 mm)
- ABS wall tool case C99V2 (445x358x254 mm)
- ABS wall tool case with 2 portable tote trays C99V3/2C (445x358x322 mm)

099000250 C99V1

Wall tool case, made from ABS, empty

Main features:

- Inner dimensions: 383x320x103
- Max. interior carrying capacity: 25 kg
- Can be padlocked

kg 25

445x358x152 mm

2,2 kg



099000350 C99V2

Wall tool case, made from ABS, empty

Main features:

- Inner dimensions: 389x320x205
- Max. interior carrying capacity: 25 kg

kg 25

2,8 kg

445x358x254 mm



099000450 C99V3/2C

Wall tool case, made from ABS, with 2 portable tote trays

Main features:

- Inner dimensions: 395x320x100
- Supplied with 2 tote trays C99C-V3, empty

kg 25

5,6 kg

445x358x322 mm



099000101 C99P

Folding tool trolley, made of aluminium

Main features:

- Ultracompact folding tool trolley, made of anodized aluminium
- Telescopic handle
- Dimensions when open: 485x520x1195 mm
- Dimensions when closed: 485x60x905 mm
- Dimensions of folding base: 485x350 mm
- Two puncture proof wheels, Ø 175 mm
- Supplied with strap

1095 mm
520 mm
485 mm

kg 100

5,8 kg



C56B


WORKBENCH WITH WOOD TOP

Main features:

- Multi-ply wood worktop with holes for a vice (1599F/125, to be ordered separately)
- Steel frame with 4 supporting legs
- Lower object shelf
- Can be fixed to floor



Ral 2011	Ral 7016	Ral 3000
056000401	056000402	056000403



kg
600



930 mm
720 mm
2000 mm

kg 54,5 kg

C59A

WORKBENCH WITH 1 CAB WITH SIX DRAWERS

Main features:

- Worktop made from multi-ply wood with holes for vice item 1599F/125 (to be ordered separately)
- 6 drawers (588x367 mm) with ball bearing slides
- Drawers protected by foamed rubber mats
- Hard-wearing nylon drawer front
- Roller cabs can accommodate thermoformed trays
- Front centralized safety lock
- Lower object shelf
- Can be fitted with paper roll holder (2400S-R/PC) and bottle holder (2400S/PF), to be ordered separately



Ral 2011	Ral 7016	Ral 3000
059000001	059000021	059000041



kg
1500



931 mm
700 mm
2000 mm

kg 115 kg



n°		kg max
4	70 mm	25 kg
1	140 mm	30 kg
1	280 mm	35 kg

C56

WORKBENCH

- Worktop made of painted sheet metal with external edge
- Steel frame with 6 supporting legs
- Two drawers with lock
- Can be fixed to floor



Ral 2011	Ral 7016	Ral 3000
056000201	056000202	056000203



kg
1200



930 mm
640 mm
2000 mm

kg 82 kg

// 056000021 **C56PL 0**

FOLDING WORKBENCH LIGHTWEIGHT RELIABLE

- Lightweight, easy to carry.
- Worktop (800x500mm) made of galvanized sheet iron, for use on one side, protected by an anti-oil and anti-petrol rubber cover.
- Handle with rubber cover, for easy transportation.
- An additional sturdy, reliable worktop, always within reach



// 18,5 kg



**EVEN LIGHTER!
ONLY 18.5 KG**

860 mm
500 mm
910 mm



// **C51** **TROLLEY**

- 3 tops covered in antislip ribbed rubber
- Two fixing options for central worktop
- Four castors Ø 100 mm:
2 fixed and 2 steering (1 with brake)

kg
200



// 21 kg



Ral 2011	Ral 7016	Ral 3000
051000001	051000002	051000003

// **C27S**

FOLDING TOOL TROLLEY FOR OUTDOOR JOBS, EMPTY

- Folding tool trolley. Its unique patented design guarantees an effortless transport
- 2 drawers, 588x277 mm, with ball bearing slides, for two-way opening
- Large lower object compartment, 588x277x220 mm
- Sheet metal frame
- 2 fixed castors, Ø 160 mm, and 2 steering castors with brake, Ø 100 mm
- Thermoplastic worktop with 6 built-in tool trays
- Centralized lock
- Can accommodate drawer partitions and MC foam tool trays



// 20 kg



Ral 2011	Ral 7016	Ral 3000
027000201	027000202	027000203

995 mm
395 mm
765 mm

n°	h	max
2	70 mm	20 kg

//C41H

TWO-MODULE TOOL TROLLEY

Main features:

- Sheet metal frame and plastic tops, synonymous with remarkable sturdiness and reduced weight
- 2 detachable modules:
 - 1 upper tool box,
 - 1 module with 2 drawers 95 mm in height,
 - 1 pull-out case made of plastic, 66 mm high, and 1 drawer 295 mm in height
- Oversized castors (160 mm), built into frame for easy transport - for example, on steps
- Side centralized lock for closing drawers of lower module
- Drawers with ball bearing slides and double closing hook
- Telescopic aluminium handle
- Small tool holder built into upper tool box
- Lower drawer with double ballbearing slide

	041000002		041000021
	041000024		041000006
	041000012		041000008
	041000010		041000005



920 mm
335 mm
536 mm

21 kg

// 021200002 C20L

Five-section cantilever tool box, made from sheet metal, empty



550x200x210 mm

5,4 kg

// 021170500 CP17

Tool box, made of stainless steel and plastic, removable tote-tray, empty



500x200x220 mm

2,5 kg



// 021203001 C20TSS

Five-section cantilever tool box, made of AISI 304 stainless steel

can be used in critical environments - that is, in areas where the minimum contamination level is not permitted -, is resistant to rust and the main acids, and can be autoclave sterilized at 121 °C.



4 kg

450x200x210 mm

// 021150201 CP15

Tool box, made from plastic, removable tote-tray and tool trays, empty

- 2 removable tool trays built into cover with adjustable partitions
- 1 interior tote-tray with adjustable partitions
- Carrying capacity: 30 kg



445x240x250 mm

2,5 kg



TOOL BAGS

020330250 **2033L/VV**

Tool case, made from aluminium, empty

- Highly shock resistant
- Nonscratch finish
- Ergonomic handle with rubber grip
- Double closure with combination
- 2 tool panels with elastic bands
- Interior bottom with removable partitions



470x375x205 mm



4,8 kg



NEW

020800100 **2080/VG**

ABS organizer tool case with swivel trays

- With upper small parts organizer (145 mm in diameter) and 4 swivel trays:
 - 1 tray 305 mm in diameter
 - 3 trays 445 mm in diameter
- Supplied complete with 12 partitions for use in 3 larger swivel trays, to obtain up to 8 compartments per level



3,4 kg

NEW

020290000 **2029/VV**

Tool case, made of thick polypropylene, aluminium edged, empty

- 2 interior tool panels



490x380x230 mm

6,1 kg

020800000 **2080/V12**

Organizer tool case with 12 removable tote-trays

Removable, folding clear tote-trays, for immediate recognition of contents



300x330x145 mm

1,8 kg



020380000 **2038/TV**

Tool trolley, made of thick polypropylene, empty

- Highly shock resistant
- Aluminium sealing profile
- Telescopic handle and big ball bearing castors
- Capacious bottom
- Document pocket
- 3 tote drawers



2 TSA approved locks with keys



2 ergonomic rubber-coated handles (including 1 side handle)



9 kg

430x500x340 mm

2 removable tool panels



021030000 C3

Mini tool bag,
made from technical fabric

Main features:

- 1 exterior front pocket with zip closure
- 2 side pockets with tote trays
- 1 convenient rear pocket with Velcro closure
- 1 removable interior tool panel, with elastic bands on both sides
- Complete with shoulder strap



330x320x150 mm

890 g



**A MINI TOOL BAG
TO ALWAYS
BRING WITH YOU!**

NEW



USB interface for
charging mobile devices



021050000 C5

Rucksack, empty

- Removable interior tool panel
- Six exterior pockets and two interior pockets
- Waterproof plastic base
- Double safety lace for fixing rucksack to shoulders
- Ergonomic padded back



2,5 kg

500x400x180 mm

021050100 C5S

Tool rucksack, made of hard-wearing polyester

- Double handle on top centre of rucksack for firm, balanced hold
- Two large front pockets
- Two capacious interior pockets
- 2 Velcro tool straps
- Handy roll-up interior bag, composed of 4 tool panels
- Adjustable reinforced shoulder straps
- Maximum carrying capacity



**TWO LARGE
FRONT
POCKETS**

900 g

370x300x100 mm



021060010 C6T

Rucksack with castors, empty

- Telescopic handle for easy transport
- Built-in castors with practical dustproof cover for use as a rucksack
- Two removable tool panels
- Interior PC pocket and five exterior pockets
- Waterproof plastic base



4,5 kg

480x370x220 mm

021110000 C11

Box, empty

- Hard water resistant plastic base
- Elastic tool bands and interior and exterior tool pockets
- Document holders built into double bottom of cover



2 kg

400x240x220 mm

021100001 C10S

420x220x250 mm

2,3 kg

Box, empty

- Hard frame
- Double bottom.
- Tilting handle for easier access to tools
- Elastic tool bands and interior and exterior pockets
- Cover
- Tool tray included in double bottom
- Can be used with trolley C8

021100000 C10

520x220x250 mm

3,3 kg



(C10 - 520 mm) (C10S - 420 mm)

020010151 2001/BZV

Tool case

made from durable technical fabric

- Double upper handle for optimal hold
- Large front document pocket with zip closure
- 20 convenient tool compartments (6 pockets and 14 elastic bands)
- Hammer loops
- Shoulder strap C9/RT can also be included (to be ordered separately)



380x290x60 mm



675 g

NEW

020010157 2001/BZ27 VU

Folding tool case with assortment of 27 tools, for universal use



Quantity/Description

- 1 electrician's scissors, straight blades
- 1 half-round needle nose pliers 180 mm
- 6 combination wrenches 7-8-10-13-17-19 mm
- 3 screwdriver for slotted head screws 3x75 - 4x100 - 5,5x150 mm
- 3 screwdriver for cross head Phillips® screws PH0x60 - PH1x80 - PH2x100 mm
- 9 offset hexagon key wrenches 1,5-2-2,5-3-4-5-6-8-10 mm
- 1 engineer's hammer 300 g
- 1 Slip joint pliers boxed joints 250 mm
- 1 measuring tape 5 m
- 1 snap - off blade utility knife 18 mm

Beta N.

- 1128BMX
- 1150
- 42
- 1201E
- 1202E
- 96/SC9
- 1370
- 1048
- 1692/5
- 1771

NEW



020050030 **2005PA/E**

Tool pouch, empty, made from nylon, with belt

- Two large pockets with elastic tool bands
- Two front scissors pockets
- Two convenient side compartments with:
 - left pocket with sturdy metal hook for measuring tapes
 - double right pocket with bag with drawstring and zip closure
- Buckle with carabine hook for adhesive tape
- Adjustable belt (70 ÷ 120 cm)



260x250x190 mm

020050035 **2005PA/ET**

1000 V

Tool pouch with assortment of 8 tools for electrotechnical maintenance

020050040 **2005PA/U**



Tool pouch with assortment of 17 tools for universal use



Quantity/Description

- 1 diagonal cutting nippers 1000V ∇ 160 mm
- 1 electrician's scissors, straight blades
- 1 mains testing screwdriver
- 2 PH1x80 - PH2x100
- 2 3.5x100 - 4.5x100
- 1 PVC electrical tape

Beta N.

- 1082MQ
1128BMX
1253
1272MQF
1274MQF
1639ESB

Quantity/Description

- 9 offset hexagon key wrenches
- 1 adjustable wrench 200 mm
- 1 Slip joint pliers boxed joints 250 mm
- 1 electrician's scissors, straight blades
- 2 screwdriver for slotted head screws 4x100 - 5.5x125 mm
- 2 screwdriver for cross head Phillips® screws PH1x80 - PH2x100 mm
- 1 measuring tape 3 m

Beta N.

- 96/SC9
111
1048
1128BMX
1201E
1202E
1692

020050060 **2005MPU**

Tool pouch, empty, made from nylon, with belt

- Five large tool pockets
- One front scissors pocket
- Buckle with carabine hook for adhesive tape
- Adjustable belt (70 ÷ 120 cm)



155x285x80 mm

020050065 **2005MPU/E**

Tool pouch with assortment of 5 tools



Quantity/Description

- 1 electrician's scissors, straight blades
- 1 half-round needle nose pliers 180 mm
- 2 screwdriver for slotted head screws 3.5x100 - 4x100 mm
- 1 screwdriver for cross head Phillips® screws PH1x80 mm



Beta N.

- 1128BMX
1150BM
1201E
1202E


42

Our epoch-making wrench 42 has a new shape.

A stylish, slim shape enhanced by a slender profile, lighter to the touch. The strength, resilience and ergonomic design of the Beta wrench reach even higher values, to provide users with the best possible tool. The manufacturing process is carried out in our factories in Sovico and Sulmona, on the basis of state-of-the-art automation technology and the best trained workers.

POWERFUL

Torque values more than doubled compared to the requirements to be satisfied under ISO 1711.



ERGONOMIC

The offset ring has a 15 degree angle to protect the hand. The shape is obtained from a die; it is not bent later.

Remarkable strength: in case of improper use, the wrench buckles, without breaking suddenly and dangerously.

CAUTION!

The new shape of wrench 42 is perfectly compatible with all the containers and trays of our epoch-making wrench 42



000421078 42/SP15

Set of 15 combination wrenches

- with holder

6-7-8-9-10-11-12-13-14-15-16-17-19-22-24 mm



000421087 42/SC9I

Set of 9 combination wrenches with compact support

- Compact, practical, easy-to-carry support
- Quickly identified wrench size
- Wrench safely locked in support

8-10-11-12-13-14-15-17-19 mm



000421070 42/S26

Set of 26 combination wrenches

6-7-8-9-10-11-12-13-14-15-16-17-18-19-20-21-22-23-24-25-26-27-28-29-30-32 mm




26x

000420478 42SLIM/B8NI

Set of combination wrenches with thin open ends, in wallet

10-11-12-13-14-15-17-19 mm



NEW

001410069 141/B9

Set of 9 ratcheting combination wrenches, straight series, in cloth wallet

8-10-11-12-13-14-15-17-19 mm



001420259 142SN/SC9

Set of 9 swivel end ratcheting combination wrenches with compact support

8-10-11-12-13-14-15-17-19 mm



001420087 142/SC9I

Set of 9 reversible ratcheting combination wrenches, with compact support

8-10-11-12-13-14-15-17-19 mm



000550164 55/B12N

Set of 12 double open end wrenches in roll-up wallet made of durable polyester

6x7-8x9-10x11-12x13
14x15-16x17-18x19
20x22-21x23-24x26
25x28-30x32 mm



111

Adjustable wrenches with scales, chrome-plated

- Movable jaw opening with right-hand rotation of pin
- Head angled at 22.5 degrees, with mm and inch scale



	L mm	A max	g		
111/100	100	15 mm	60	001110010	
111/150	150	24 mm	165	001110015	
111/200	200	28 mm	325	001110020	
111/250	250	34 mm	505	001110025	
111/300	300	35 mm	790	001110030	
111/450	450	54 mm	2043	001110045	
111/600	600	62 mm	3300	001110060	

001860008 186 8-32

Self-locking wrench with automatic take-up device for hexagons, 8 to 32 mm

Ideal for hexagon, Spline, square and Torx® head screws, including damaged screws.



001950066 **195/B5**

Set of 5 reversible ratcheting double-ended angle head wrenches

in wallet

8x10-12x13-14x15-16x18-17x19 mm



000960374 **96/SC9** ○

Set of 9 ball head offset hexagon key wrenches


○ mm	L mm
1,5	45
2	50
2,5	57
3	64
4	72
5	83
6	94
8	105
10	119



000960354 **96BPC/SC9** ○

Set of 9 ball head offset hexagon key wrenches


○ mm	L mm
1,5	79
2	85
2,5	89
3	100
4	110
5	129
6	152
8	173
10	194



000970164 **97BTX/SC8** ☆

Set of 8 ball head offset key wrenches, long model, for Torx® head screws


○ mm	L mm
T9	65
T10	74
T15	84
T20	96
T25	98
T27	109
T30	123
T40	136



000961354 **96LBP/SC9** ○

Set of 9 ball head offset hexagon key wrenches

○ mm	L mm
1,5	91
2	100
2,5	113
3	130
4	142
5	163
6	185
8	205
10	231




**EXTRA LONG
VERSION
+30%**



000970364 **97BTXL/SC8** ☆

Set of 8 ball head offset key wrenches, long model, for Torx® head screws

○ mm	L mm
T9	83
T10	89
T15	103
T20	114
T25	130
T27	145
T30	166
T40	183



**EXTRA LONG
VERSION
+25%**



THE FIRST ONE

Rapid and easy to handle.
The small-size handle can be perfectly balanced to quickly rotate in the palm of the hand.
The ergonomic shape allows the wrench to be used for extremely high torques as well.
The hexagon ends are designed to transmit the maximum possible torque to the screw.



BLADE PASSES THROUGH HANDLE

000960946 **96T/S5P**



Set of 5 offset hexagon key wrenches with handles

○ 2,5-3-4-5-6 mm



000970791 **97TTX/S6**



Set of 6 ball head offset key wrenches for Torx® head screws with handles


○ T10-T15-T20-T25-T30-T40



009510687 **951/S6**

Set of 6 T-handle wrenches with three hexagon male ends

○ 2,5-3-4-5-6-8 mm



2,5÷6 mm

THE ORIGINAL ONE


When this wrench was launched, back in 1980, it was a revolution. Designed to work on high-resistance screws, it is the name for quick handling, accurate fit and flexible use.

The hexagon T handle can be adjusted as required.

The hexagon ends are designed to transmit the maximum possible torque to the screw.

The rod length allows remarkable torques to be effortlessly applied to the screws.

Ongoing production improvements have translated, for example, into sandblasted finishes and sharp-edged hexagon ends which allow a better fit onto any screws, including damaged ones. Laser marking results in a sturdier rod.



THE RELIABLE ONE


Reliable, precise pre-positioning is the secret for the success of this wrench.
The articulated joint maintains its function over the years, no adjustment being required.
Socket rotation angle: 50°.
Can be used at 90° in fixed position.
Sliding T-handle, can be stopped in the required position throughout its length.
Triple size marking on head.

009520079 **952/D7**



Serie di 7 chiavi a T con bussola esagonale snodata

○ 7-8-10-12-13-14-17 mm





THE EVOLUTION OF THE SCREWDRIVER!

012031018 1203E/D8P

Set of 8 screwdrivers
 1201E 2,5x50-3x75-4x100-5,5x100
 6,5x150 mm
 1202E PH0x60-PH1x80-PH2x100 mm

012071207 1207E/TX-D7

Set of 7 screwdrivers
 1207E/TX T6-T8-T10-T15
 T20-T25-T30

012031019 1203E/D10N

Set of 10 screwdrivers
 1201E 2,5x50-3x75-4x100-5,5x150
 6,5x150 mm
 1202E PH0x60-PH1x80-PH2x100 mm
 1201E/N 0,8x4x30 mm
 1202E/N PH1x4,5x30 mm

012630008 1263/D8

Set of 8 screwdrivers
 1260 2,5x50-3x75-4x100-5,5x125
 6,5x150 mm
 1262 PH0x60-PH1x80-PH2x100 mm

012630010 1263/D10

Set of 10 screwdrivers
 1260 3x75-3,5x100-4x125-5,5x150-6,5x150 mm
 1262 PH0x60-PH1x8-PH2x100 mm
 1260N 4x30 mm
 1262N PH1x30 mm

012670307 1267TX/D7

Set of 7 screwdrivers
 1267TX T6-T8-T10-T15
 T20-T25-T30



012930401 1293/D6

Set of 6 screwdrivers
 1290 0,6x3,5x75-1x5,5x150
 1,2x6,5x150 mm
 1292 PH0x3x60-PH1x4,5x80
 PH2x6x100 mm



Betamax
 MAXIMUM PERFORMANCE

012930408 1293INOX/D8

Set of 8 screwdrivers made of stainless steel

1290INOX 2,5x50-3x75-4x100
 5,5x150-6,5x150 mm
 1292INOX PH0x60-PH1x80-PH2x100 mm



Beta
INOX
 STAINLESS STEEL

000961619 **96BP-CL/SC9** ○

Set of 9 ball head offset key wrenches, coloured


Ø mm	L mm
1,5	91
2	100
2,5	113
3	130
4	142
5	163
6	185
8	205
10	231

**EXTRA LONG
VERSION
+30%**



000971658 **97BTX-C/SC8** ☆

Set of 8 coloured ball head offset key wrenches, for Torx® head screws



Ø mm	L mm
T9	80
T10	86
T15	90
T20	95
T25	100
T27	105
T30	114
T40	124



001422087 **142MC/SC9I** ○

Set of 9 reversible ratcheting combination wrenches, coloured, with compact support

Ø mm	L mm
8x8	136
10x10	159
11x11	168
12x12	174
13x13	180
14x14	190
15x15	200
17x17	233
19x19	248




COLOR

ONE COLOUR, ONE SIZE

009202964 **920MC/C14** ○ 12"

14 coloured hexagon hand sockets and 5 accessories, in metal case




420x185x60 mm

4,2 kg

920MC	8-10-11-12-13-14-15-16-17-18-19-21-22-24 mm
920/21	125 mm
920/22	255 mm
920/25	
920/42	
920/55	

009002960 **900MC/C24** 14"

Assortment of 11 hexagon sockets, 13 coloured socket drivers and 6 accessories, in metal case



270x120x45 mm

1 kg

900MC	4-5-6-7-8-9-10-11-12-13-14 mm
900MC/PH	PH1 - PH2 - PH3
900MC/TX	T10-T15-T20-T25-T27-T30- T40
900MC/LP	0,8x4 - 1,2x6,5 - 1,2x8 mm
900/20	50 mm
900/21	150 mm
900/25	
900BG/30	
900/42	
900/55	

CODE

ONE COLOUR, ONE TIP STYLE

007202913 **720MC/C13** 12"

Set of 13 impact sockets, 1/2" female drive, coloured, phosphatized, in metal case



335x145x60 mm

2,4 kg

012570210 **1257LPH/S8** 1" +

Set of 8 micro-screwdrivers for slotted head screws and Phillips® screw in hard case

1257PH + PH00-PH0-PH1
1257LP 0,4x2-0,4x2,5-0,5x3
0,6x3,5-0,8x4 mm



180x120x50 mm

012632008 **1263MC/D8** 1" +

Set of 8 coloured screwdrivers

1260 2,5x50-3x75-4x100- 5,5x125
6,5x150 mm
1262 PH0x60-PH1x80
PH2x100 mm



012672307 **1267MC/TX-D7** 1/4"

Set of 7 screwdrivers for Torx® head screws, coloured

1267TX T6-T8-T10-T15-T20-T25-T30



008600880 **860/C27** 1/4"

25 bits, 1 connector and 1 reversible ratchet in plastic case

860LP 0,5x3-1,0x5,5-1,2x6,5 mm
860PE 2-2,5-3-4-5-6 mm
860PH PH1-PH2(x2)-PH3
860TX T6-T8-T10-T15-T20-T25-T30-T40
860PZ PZ1 - PZ2(2x) - PZ3
860/55 100 mm
892/0



008600902 **860MIX/A31** 1/4"

Set of 30 bits with magnetic bit holder in plastic case

860LP 0,5x3 - 0,6x4,5 - 0,8x5,5
1,0x5,5 - 1,2x6,5 mm
860PE 2-2,5-3-4-5-6-8-10 mm
860PH PH0 - PH1 - PH2 - PH3 - PH4
860RTX T9-T10-T15-T20-T25-T27-T30-T40
860PZ PZ1 - PZ2 - PZ3 - PZ4
882MSR/50 1/4" 1/4"



//861PB

Set of 6 bits in fabric bracelet with magnetic clasp

// 008610956 MIX1

- ⊕ 861PH PH1 - PH2
- ⊕ 861PZ PZ1 - PZ2
- 861PE 4 - 5 mm



// 008610966 MIX2

- ⊕ 861PH PH2
- ⊕ 861PZ PZ2
- ⊕ 861TX TX20 - TX25 - TX30 - TX40



// 008620950 862F/A7 1/4

Set of 7 magnetic bits, hexagon sockets, in plastic case



862F ○ 5,5-6-7-8-10-12-13 mm

// 008670901 867/C52 10 mm

52 hexagon bits, 10 mm and 2 accessories

	867PE	○ 4-5-6-7-8-10-12 mm
	867PE/L	○ 4-5-6-7-8-10-12 mm
	867XZN	○ M5-M6-M8-M10-M12
	867XZN/L	○ M5-M6-M8-M10-M12
	867TX	⊕ T20-T25-T30-T40-T45-T50-T55
	867TX/L	⊕ T20-T25-T30-T40-T45-T50-T55
	867RTX	⊕ T20-T25-T30-T40-T45-T50-T55
	867RTX/L	⊕ T20-T25-T30-T40-T45-T50-T55
	867/1	○ 10 mm - □ 3/8"
	867/2	○ 10 mm - □ 1/2"



250x170x70 mm

2,1 kg

// 016000008 1600Q 8 1/4

Four-way wrench for control panel operators

Wrench for use for maintenance jobs in countless industries, e.g. electronics, hydraulics, ventilation and gas.



// 016000010 1600Q 10 1/4

Eight-way wrench, with articulated joint, for control panel operators

- Eight-way wrench, can be rotated to easily select the head to use.
- Magnetic articulated joint for increased force.
- 1/4" male drive for use of sockets.
- Wrench for use for maintenance jobs in countless industries, e.g. electricity, hydraulics, ventilation and gas.



// 012560100 1256/C36-2

Bi-material microscrowdriver with 36 interchangeable 4-mm bits and magnetic extension

	1256TX	⊕ T3-T4-T5-T6-T7-T8-T9-T10-T15
	1256RTX	⊕ T6-T7-T8-T9-T10
	1256LP	● 0,8-1,2-1,5-1,8-2-2,5-3-3,5-4 mm
	1256PE	○ 0,7-0,9-1,3-1,5-2 mm
	1256PH	⊕ PH000-PH00-PH0-PH1
	1256PZ	⊕ PZ000-PZ00-PZ0-PZ1
	1256/20	
	1256/30	



130x60x35 mm

200 g

009000882 **900/55Z**


1/4" drive reversible ratchet,
72 tooth mechanism

5° TAKE-UP ANGLE

72 TOOTH
MECHANISM
MORE COMPACT
RATCHET HEAD



15 teeth
in contact
with gear
at all times




L mm	Ø mm	A mm	■
126	25	23	1/4



Reversible ratchet



	L mm	Ø mm	A mm	■	g		
910/55	200	30	33	3/8"	239	009100882	
920/55	275	40	43	1/2"	475	009200882	



009000971 **900/C11** 14" 14"

11 hexagon sockets, 20 bits and 8 accessories,
in metal case

	861LP	⌀	0,5x3-0,8x5,5-1x5,5-1,2x6,5 mm
	861PE	○	3-4-5-6-8 mm
	861PH	⊕	PH0-PH1-PH2-PH3
	861TX	⊗	T8-T10-T15-T20-T25-T30-T40
	895/1	○	1/4" - 1/4"
	900	○	5-5,5-6-7-8-9-10-11-12-13-14 mm
	900/16	□	1/4" - 1/4"
	900/20		50 mm
	900/21		150 mm
	900/25		
	900/42		
	900BG/30		
	900/55	⊗	

270x120x45 mm



1,2 kg

009020807 **902A/C22** 12" 14"

Assortment of 22 hexagon sockets
and 6 accessories, in metal case

1/4"		900	○	5-5,5-6-7-8-9-10-11-12-13 mm
		900/20		50 mm
		900/25		
		900/55	⊗	
1/2"		920A	○	10-13-14-15-17-18-19-22-24 27-30-32 mm
		920/21		125 mm
		920/25		
		920/55	⊗	



420x185x60 mm

3,5 kg

Assortment of 16 hexagon sockets and 5 accessories in foam tray, in metal case

	910A	○	6-7-8-9-10-11-12-13-14-15-16-17-18-19-21-22 mm
	910/21		125 mm
	910/22		250 mm
	910/25		
	910/42		210 mm

38"



335x145x60 mm

009100936 **910A/C16** 38"

Reversible ratchet (910/55)



009100935 **910A/C16HR** 38"

Reversible ratchet with rotating handle (910/58)



Assortment of 17 hexagon sockets and 5 accessories in foam tray, in metal case

	920A	○	10-11-12-13-14-15-16-17-18-19-20-21-22-24-27-30-32 mm
	920/21		125 mm
	920/22		255 mm
	920/25		
	920/42		305 mm

12"



420x185x60 mm

009200924 **920A/C17M** 12"

Reversible ratchet (920/55)



009200937 **920A/C17MR** 12"

Reversible ratchet with rotating handle (920/58)



009280955 **928A/C12** 34"

Assortment of 12 hexagon hand sockets and 5 accessories, in metal case



	928A	○	22-24-27-30-32-34-36-38-41-46-50-55 mm
	928/21		200 mm
	928/22		380 mm
	928/25		
	928/42		450 mm
	928/55	⊗	



530x220x80 mm

//605E 1/4"

Click-type torque wrenches with reversible ratchets for right-hand and left-hand tightening torque accuracy: $\pm 6\%$

UNI EN 26789 ISO 6789



	Nm mm	kgfm	lbf.in	■	L (mm)	g		
605E/5	1÷5	0,1÷0,5	10÷45	1/4"	190	180	006050105	
605E/10	2÷10	0,2÷1,0	18÷90	1/4"	190	180	006050110	

//666N

Click-type torque wrenches with reversible ratchets, for right-hand tightening, torque accuracy: $\pm 3\%$

- Scale increased by 60% for improved visibility and setting accuracy
- Torque adjusting speed increased by 40%
- Red colour of o-ring indicates that wrench is unlocked and torque can be adjusted

- Handle and lens materials resistant to all chemical substances used in automotive sector, industry and aviation

UNI EN 26789 ISO 6789



	Nm mm	kgfm	lbf.in	■	L (mm)	g		
666N/2	5÷25	0,5÷2,5	4÷18	1/4"	220	300	006660002	
666N/2X	5÷25	0,5÷2,5	4÷18	3/8"	220	300	006660003	
666N/5	10÷50	1÷5	7÷37	3/8"	325	660	006660005	
666N/10	20÷100	2÷10	15÷75	3/8"	367	730	006660010	
666N/10X	20÷100	2÷10	15÷75	1/2"	367	800	006660011	
666N/20	40÷200	4÷20	30÷150	1/2"	465	1010	006660020	
666N/30	60÷300	6÷30	50÷220	1/2"	581	1380	006660030	



//674/C

Click-type torque bars, round drive $\emptyset 22$ mm, for right-hand and left-hand tightening, torque accuracy: $\pm 4\%$, in case

- Dual scale for accurate torque adjustment
- Safety knob for maintaining set torque value
- When not in use, set torque to lowest value of torque wrench range

ROUND DRIVE
 $\emptyset 22$ mm

NEW



UNI EN ISO 6789



006740005 674/C50

006740008 674/C80

006740010 674/C100

Nm	kgfm	Lbf.ft	L mm	kg
100÷500	10÷50	80÷400	786	3,4

Nm	kgfm	Lbf.ft	L mm	kg
160÷800	16÷80	120÷600	997	4,5

Nm	kgfm	Lbf.ft	L mm	kg
200÷1000	20÷100	150÷750	997	4,5

//677/C 3/4"

Break-back torque wrenches with push-through ratchets, for right-hand and left-hand tightening, torque accuracy: $\pm 4\%$ in case

UNI EN 26789 ISO 6789

677/C100



	Nm mm	kgfm	lbf.in	■	L (mm)	kg		
677/C50	100÷500	10÷50	70÷350	3/4"	915	5,2	006770606	
677/C70	150÷700	15÷70	100÷500	3/4"	1140	6,2	006770611	
677/C100	300÷1000	30÷100	200÷750	3/4"	1470	7,5	006770615	

UNI EN 26789 ISO 6789



//006100025 610/5 12"

Click-type torque wrenches with reversible ratchets, for right-hand tightening, with 5 preset values, torque accuracy: $\pm 4\%$

- Selectable torque values: 90 - 100 - 110 - 120 - 130 Nm
- Pull handle end to unlock wrench and select required tightening torque
- When not in use, set torque to lowest value of torque wrench range



SUITABLE FOR TYRE REPAIRERS

//006100125 610L/5 12"



Click-type torque wrenches with L-shaped levers, for right-hand tightening, with 5 preset values, torque accuracy: $\pm 4\%$

- Selectable torque values: 90 - 100 - 110 - 120 - 130 Nm
- Pull handle end to unlock wrench and select required tightening torque
- When not in use, set torque to lowest value of torque wrench range

CE //665 12" 30"

Mechanical torque wrench with digital setting and reversible ratchet, for right-hand tightening, torque accuracy $\pm 3\%$

- Auto power off after 30" when torque is set under minimum torque threshold
- Display will remain on with set torque value
- Torque setting to decimal digit
- Power supply: 1 battery 3V (included)



QUICK, ACCURATE DIGITAL TORQUE ADJUSTMENT

UNI EN 26789 ISO 6789

	Nm mm	■	D (mm)	A (mm)	L (mm)	g		
665/6	10÷60	3/8	30	33	335	655	006650006	
665/10	20÷100	3/8	30	33	375	725	006650010	
665/10X	20÷100	1/2	30	37	375	725	006650011	
665/20	40÷200	1/2	40	43	470	995	006650020	
665/30	60÷330	1/2	40	43	590	1260	006650030	

//006650100 665/SW CE

Digital torque calibration device

Device allows calibration of wrenches item 665 with help of torque meters 680 and 682, without having to dismantle wrench. Fitted with a micro USB port, for firmware updates.



THE DECENTRALIZED PIN ALLOWS THE FULCRUM TO BE CLOSER TO THE CUTTING POINT, THEREBY RESULTING IN AN IMPROVED LEVER EFFECT.

011690133 1169BM/D3

Set of 1 combination pliers,
1 long needle nose pliers and
1 diagonal cutting nippers



011690273 1169GBM/D3

Set of 1 combination pliers,
1 long needle nose pliers and 1 diagonal cutting
nippers, bi-material handles, industrial finishing




011690014 1169/D4

Set of 1 combination pliers,
1 long needle nose pliers,
1 cutting nippers and 1 slip joint
pliers with boxed joints



010310000 1031/S4

Set of 4 circlip pliers



011500618 1150HPC

Heavy duty universal pliers with cutting
edges made of sintered steel

- The decentralized pin allows the fulcrum to be closer to the cutting point, thereby resulting in an improved lever effect.
- Perfect alignment of the nose and the thin profile allow the pliers to be used in very small areas.
- The body of the pliers is made of a reliable molybdenum steel which has been heat treated in order to be flexible and resistant so as to guarantee a safe grip in any moment.

PATENTED




ABSOLUTELY GROUNDBREAKING
REMARKABLE CUTTING CAPACITY

Hardness of M2 steel cutting edges =	-73%
Shearing stress - static test =	+127%
Average life of cutting edges = (test ISO 5744)	65HRC

1048

Slip joint pliers, boxed joints



9-POSITION MODEL

010480010 1048 175

L 175 mm	ø Max 32 mm	Max 30 mm
----------	-------------	-----------

010480015 1048 250

L 250 mm	ø Max 50 mm	Max 48 mm
----------	-------------	-----------


010480020 1048 300

L 300 mm	ø Max 58 mm	Max 56 mm
----------	-------------	-----------

010470240 1047/240

Slip joint pliers, push button alignment


- Quick, accurate adjustment by pressing push button
- No accidental misadjustment
- Heat-treated jaws



L 240 mm	ø Max 36 mm	Max 32 mm
----------	-------------	-----------

1052

Adjustable self-locking pliers, concave jaws



	L mm	ø Max mm	g		
1052/140	140	22	175	010520014	
1052/190	190	36	360	010520019	
1052/240	240	42	590	010520024	
1052/300	300	55	900	010520030	

004370550 437U/09

Assortment for repairing damaged threads in wooden case

M5X0,8
M6X1,0
M8X1,25
M10X1,5
M12X1,75



370x230x55 mm

004370003 437P

Thread dresser, for repairing internal and external, right-hand and left-hand threads

P 0,80÷3,00 mm



010090060 1009L/DP-S2

Set of 2 extra-long, knurled double swivel nose pliers

L 340 mm



45°

1009L/D

1009L/DP



004120469 412M/SP19

Set of 19 twist drills with cylindrical shanks, HSS, AISI M2, entirely ground finishing

- Self-centring
- High performance and cutting accuracy
- For drilling alloy steel, cast iron and metal in general

Ø 1÷10 x 0,5 mm

R ≤ 850 N/mm²
HV ≈ 820
DIN 338



115x170x40 mm

004150440 415CO/SP19A

Set of 19 twist drills with cylindrical shanks, HSS-CO 5%

- For drilling holes into STAINLESS steel, alloy steel, cast iron, mild steel, light alloys

Ø 1÷10 x 0,5 mm

R ≤ 1400 N/mm²
HV ≈ 850÷920
DIN 338



115x170x40 mm

004120415 412/SP25P

Twist drills with cylindrical shanks, short series, HSS, entirely ground glossy finishing

Ø 1÷13 x 0,5 mm

R ≤ 700 N/mm²
HV ≈ 750÷820
DIN 338



115x170x40 mm

004460060 446/C110

Assortment of 105 chrome-steel taps and dies, metric thread, and 5 accessories for car repair jobs in wooden case

435/0 444/1 436/1
435/3 444/2



430 M mm	433 M mm	440/440A M mm	441/441A M mm
2x0,4	6x0,75 - 7x0,75	2x0,4	6x0,75 - 7x0,75
3x0,5	8x0,75 - 8x1	3x0,5	8x0,75 - 8x1
4x0,7	9x0,75 - 9x1	4x0,7	9x0,75 - 9x1
5x0,8	10x0,75 - 10x1	5x0,8	10x0,75 - 10x1
6x1	10x1,25 - 11x0,75	6x1	10x1,25 - 11x0,75
7x1	11x1 - 11x1,25	7x1	11x1 - 11x1,25
8x1,25	12x0,75 - 12x1	8x1,25	12x0,75 - 12x1
9x1,25	12x1,25 - 12x1,5	9x1,25	12x1,25 - 12x1,5
10x1,5	14x1 - 14x1,25	10x1,5	14x1 - 14x1,25
11x1,5	14x1,5 - 16x1	11x1,5	14x1,5 - 16x1
12x1,75	16x1,5 - 18x1,5	12x1,75	16x1,5 - 18x1,5
14x2		14x2	
16x2		16x2	

500x337x60 mm

004530107 453C/C7

Set of 7 core drills with Weldon shanks, short series, HSS-G

Ø 12-14-16-18-20-22
+ ejector
R ≤ 850 N/mm²



160x145x57 mm

004110197 411/K7

Set of 7 multi-purpose drills, for cutting all materials, entirely ground, with U-shaped slots
With sharp plate and innovative geometry

Ø 3÷10 mm
HVA~1650
HRC~40÷50



160x98x18 mm

004250600 425E/SP3

Set of 3 stepped drills, HSS-G, enhanced grinding efficacy

Ø 4÷12 ; 4÷20 ;
4÷30 mm
R ≤ 800 N/mm²
HV 820



110x150x40 mm

NEW

BETA'S PULLER 1517C

relies on a leg self-locking mechanism triggered by the spring on the crosspiece. This feature makes it easy to position and lock the puller on the part to remove. After the puller has been fixed in place, the legs can be locked by means of the ring nut.

The peculiar crosspiece has 4 seats which allow the 1517C puller to be used with both 2 legs – for easier, quicker jobs – and 3 legs – for increased firmness. The shear pin on the screw head breaks when the maximum permissible torque is exceeded, thereby protecting the puller from overloads.

//1517C

Combination two/three-leg self-locking pullers

- Leg holder with configuration for 2- or 3-leg use
- Simultaneous leg opening
- Self-locking effect
- With shear pin
- Size 2 with screw extension (total length of screw with extension: 380 mm)



	A min÷Max mm min÷Max mm	L mm	L1 mm	mm		
1517C/0	12÷140	145	250	18	015170500	
1517C/1	20÷180	200	300	18	015170501	
1517C/2	30÷280	270	300	18	015170502	

//1502

Two-leg universal pullers with quick leg adjustment and closure

Specifications:

- For both internal and external use
- Legs can be moved along crosspiece
- Legs are locked by means of a quick lever release mechanism

QUICK LEVER RELEASE MECHANISM



	A min÷Max mm	A1 min÷Max mm	L mm	L1 mm	mm		
1502/0	40÷90	80÷130	100	166	17	015020000	
1502/1	50÷130	90÷170	100	166	17	015020001	
1502/2	65÷150	115÷210	150	247	22	015020002	
1502/3	65÷190	125÷260	150	247	22	015020003	
1502/4	70÷235	170÷335	200	321	27	015020004	




NEW

// 015450011 1545/C5M

Puller 1542/1 with 5 extractors 1544

	A mm	C mm
1544/1	9÷12	0,80
1544/2	13÷17	1,15
1544/3	16÷21	1,70
1544/4	20÷25	1,65
1544/5	25÷30	2,00



265x180x45 mm

// 014300105 1430/S5

Set of 5 tapered extractors for brown screws and studs, made from hardened steel in case


1430/1-1430/2-1430/3
1430/4-1430/5



110x150x40 mm

// 000310420 31BM/D6

Set of 6 pin punches
with handles
Ø 2-3-4-5-6-8 mm



// 000320160 32AU

Automatic centre punches



L 150 mm



// 1370

Mechanic's hammers
wooden shaft

	g	g		
1370/300	300	439	013700053	
1370/500	500	669	013700055	
1370/800	800	949	013700058	
1370/1000	1000	1180	013700060	
1370/1500	1500	1722	013700065	
1370/2000	2000	2181	013700070	



UNI 7778 DIN 1041

// 1370T

Mechanic's hammers
fibre shaft

	g	g		
1370T/300	300	452	013700630	
1370T/500	500	663	013700650	
1370T/800	800	1017	013700680	
1370T/1000	1000	1279	013700700	
1370T/1500	1500	1740	013700750	



// 1390

Soft face hammers,
wooden shafts

	Ø mm	g		
1390/22	22	134	013900022	
1390/28	28	230	013900028	
1390/35	35	365	013900035	
1390/45	45	698	013900045	
1390/60	60	1462	013900060	



UNI 7784

016970030 **1697 30**



**Cross laser level,
30 metres, green beam,
with magnetic base and wall-mount bracket,
in case**

TECHNICAL SPECIFICATIONS:

- self-levelling cross
- self-levelling function can be switched off for manual use
- laser diode 515 Nm, class 2
- working range: 30 m
- accuracy: ± 1 mm at 5 m
- self-levelling range: $3^\circ \pm 0.5^\circ$
- body made of ABS and nonslip rubber
- 1/4" female drive
- 2xAAA batteries
- battery life: 4 hours



320x230x90 mm

BASE:

- 1 magnetic base for individual and combined use, 1/4" male drive
- 1 adjustable tightening bracket for several wood and metal profiles (for use in combination with magnetic base)
- quick horizontal and vertical alignment at a 90° angle



NEW



016930020 **1693 20**

**Laser distance meter,
20 m**

MEASUREMENTS:

- single distance measurement
- continuous measurement or minimal measurement
- Auto off feature
- Battery life: up to 4,000 measurements

TECHNICAL DATA

Measurement range:
0.05 ÷ 20m (0.2in ÷ 66ft)
Scale selection: m, in, ft
Measurement accuracy:
 ± 1.5 mm (± 0.06 in)
Laser class: 2
Battery: AAA 2 x 1.5



100 mm
23 mm
36 mm

80 m



016930080 **1693M 80**

**Laser distance meter, multipurpose,
80 m**

MEASUREMENTS:

- single distance measurement
- continuous measurement or minimal measurement

FUNCTIONS:

- addition/subtraction
- area measurement
- volume measurement
- indirect measurement (Pythagorean measurement)
- tilt measurement

- Auto off feature
- Soft cloth case (included)
- Battery life: up to 4,000 measurements

TECHNICAL DATA

Measurement range:
0.05 ÷ 80 m (0.2 in ÷ 229 ft)
Scale selection: m, in, ft
Measurement accuracy:
 ± 1.5 mm (± 0.06 in)
Laser class: 2
Max. storage: 99 units
Battery: AAA 2 x 1.5V




//1650

Sliding gauge made from hardened stainless steel

- Reading to 0.05 mm
- Spring locking

DIN 862

UNI EN ISO 13385-1



A MAX 150 mm L 225 mm

016500001 1650/150

A MAX 200 mm L 290 mm

016500002 1650/200

//363

Heavy duty pipe wrenches made from light alloy



	L m	Ø (")	Ø (mm)		
363 350	350	2" gas	60	003630035	
363 450	450	2 1/2" gas	76	003630045	
363 600	600	3" gas	90	003630060	
363 900	900	5" gas	140	003630090	

//017500100 1750KG10

Lever-operated grease gun, 10 kg, with high-pressure hose, 2 m

Complete with swivel fitting, to avoid choking hose

Die-cast aluminium pump body with check valve

3 different pressure levels available:

- 4 g at 275 bar
- 7 g at 206 bar
- 9 g at 137 bar



//003420030 342

Ratchet-type shears for plastic pipes



Ø 0÷42 mm
1 5/8"

//017500500 1750

Lever operated grease guns, 500 cc



550 Bar

018600255 **1860RG**

Adjustable magnetic square, 30°÷270°

- Ideal for locking tubular or flat parts
- 15 kg magnetic force
- Supplied with an offset hexagon key wrench for locking angle adjustment mechanism
- Supplied with a pin for locking angle adjustment mechanism at 30°-45°-90°/270°-180°
- With hexagon hole making it easier to separate magnet from metal



30°÷270°



15 kg



018600210 **1860SQ**

Magnetic square, 45°/90°


- Ideal for locking tubular or flat parts
- 25 kg magnetic force
- No battery required, ON/OFF effect obtained by tilting interior magnets
- Easier chip removal with magnets in OFF position



45°/90°



25 kg



018270100 **1827/K**

Gas soldering iron with 7 accessories in case with soft polyethylene foam base

- Power: 30 watts to 125 watts
- Tip temperature can be adjusted between 250 °C and 500 °C
- Gas flow regulator
- Warm-up time: 15 seconds
- Tank contains gas for 120 minutes' non-stop operation
- Clear tank for monitoring gas level
- Can be refilled with butane gas



018600290 **1860EI**

Magnetic square, 90°, for interior and exterior angles

- Ideal for locking tubular or flat parts
- 18 kg magnetic force
- With bevels for 30° and 60° angles
- With hexagon hole making it easier to separate magnet from metal



90°



18 kg

TEMPERATURE RANGE
-20 ÷ +600°C



IP54 (CE)

017600710 **1760/TMC**

Infrared thermal camera

Compact thermal camera for contactless temperature measurement, suitable for applications in building, mechanical, electric installation and heating industries

- LCD TFT display, 2", 240x320
- Sensor, 32x32 pixels
- Acquisition frequency 7Hz
- Thermal sensitivity <347mK
- Automatic acquisition of hot and cold spots camera for acquisition of images in BMP format (max. 100 images) adjustable emissivity
- Power supply: 3 alkaline AAA batteries
- USB interface
- IP54
- Temperature range: -20 °C ÷ +600 °C
- Infrared band: 6.5÷14µm
- Visible/infrared image fusion: 0.5; 1; 2m
- Alarm function, selecting acceptable maximum and minimum temperatures

070420001 **7042LCD**

Auto-darkening LCD mask, for electrode welding; MIG/MAG; TIG and plasma. Solar cells power supply and lithium batteries for outstanding LCD filter life

- Viewing area: 98x43 mm
- Darkening shade: DIN 9-13, externally adjustable
- UV/IR protection
- Light to dark time: 1/25000 s
- Dark to light time: 0.25-1s
- Adjustable darkening sensitivity and delay
- Auto on/off
- Grinding feature
- Optimized shape to make it easier to breathe with pulled-down screen



070410001 **7041LCD/4S**

Auto-Darkening LCD mask, for electrode welding; MIG/MAG; TIG and plasma. 4 sensors with TRUE COLOR filter. Solar cell power supply and lithium batteries for outstanding LCD filter life.

- Viewing area: 98x80 mm
- Darkening shade range: 5÷8.5/ 9-13, internally adjustable
- UV/IR protection: DIN16
- Light to dark time: 1/25000 s
- Dark to light time: 0.1-2.0s
- Adjustable darkening sensitivity and delay
- Auto on/off
- Grinding feature
- Low battery indicator
- Ergonomic design, lightweight, well-balanced
- With adjustable ring nut



070430001 **7043**

Auto-darkening LCD mask, for electrode welding, MIG/MAG, TIG and plasma, solar cell power supply

- Viewing area: 92x43 mm
- Darkening shade: DIN 9-13, externally adjustable
- UV/IR protection
- Light to dark time: 1/1000 s
- Dark to light time: 0.1-1.0 s
- Adjustable darkening delay
- Auto on/off
- Grinding feature
- Optimized shape to make it easier to breathe with pulled-down screen




018520175 **1852R1750**

Portable induction heater

- Heats and loosens stubborn bolts, hubs and bearings without using flames
- Allows any type of ferromagnetic metal to be heated

MAXIMUM SAFETY WITHOUT USING FLAMES



480x370x130 mm



Technical data:

- Input voltage: 230V AC, 50/60 Hz
- Input current: max. 7.5 A
- Power: max. 1.75 kW

BENEFITS

- 1 Time saving: quick, extremely accurate heating
- 2 Fire safety: does not produce flames, maximum operator safety
- 3 Functional: can be used with one hand, and coils can be easily interchanged

FIELDS OF APPLICATION

- Automotive industry
- Industrial maintenance
- Aviation industry
- Naval industry
- Petrochemical industry

Standard equipment:

- (1) Two front attachable coils, Ø 19 and 26 mm, for loosening nuts
- (3) One flat coil for heating surfaces
- (2) One flexible coil, 800 mm long
- Supplied in plastic case

017600020 **1760/RMS**

Industrial digital multimeter accurate and sturdy, in a 6-mm co-moulded shell, with antislip, shockproof outer rubber part

- Water protection IP67
- Protection up to 1000V
- Tested for accidental falls up to 2 m
- Protected inlets • Autoranging
- Large direct reading display, backlit, blue
- K type temperature probe (included)
- Self-power down
- Rubber terminal base for enhanced operating comfort
- Double insulated terminals, 1000V, 1 m long
- Supplied in a soft case
- CAT IV 600V/ CAT III 1000V
- Actual effective value TRUE RMS



	Measuring range	Base accuracy
AC/DC voltage	110mV – 600V ±0.8%	- ±2% rdg
AC/DC current	110µA – 10A ±1.5%	- ±2% rdg
Resistance	110Ω – 40MΩ ±1.2%	- ±2.5% rdg
Capacity	11nF – 40mF ±5%	- ±10% rdg (up to 11mF)
Frequency	1100Hz – 110 MHz ±1.2%	- ±1.5% rdg
Temperature	-32°C – +1000°C ±3%	- ±5% rdg
Diode test	3V DC ±10% rdg	
Continuity test	<30 Ω	



011490010 **1149F**

Front wire stripping pliers with cutting blade, self-adjusting



0,2÷6 mm²

016090101 **1609B**

Mechanical crimping pliers

- For noninsulated copper terminals, 10÷120 mm²
- Antislip rubber handle
- Internal "H" section pin for unparalleled punch smoothness
- Made from burnished steel



10÷120 mm²

1740B

Compact heavy-duty riveting pliers

- Optimized lever ratio for increased compactness and handiness.
- 3 jaws lock rivet for a perfect grip.
- Adjustable head for pulling rivet by 2 to 5 leg movements.



2,4÷4,8 mm steel

017400280 **1740B 280**



2,4÷6,4 mm steel

017400330 **1740B 330**



3 JAWS:
IMPROVED
RIVET GRIP



L 330 mm

WITH
STEM TANK

L 600 mm

017410000 **1741B**

Riveting pliers supplied with 4 interchangeable nozzles



L 250 mm

017410450 **1741U**

Ultra compact riveting pliers with adjustable force with 4 interchangeable nozzles



**3 JAWS:
IMPROVED
RIVET GRIP**



L 200 mm

017490005 **1749AC**

High thrust gun for chemical binders



230 mm
STANDARD Ø 50 mm

017490010 **1749A**

Bonding gun, professional model aluminium tube



018700220 **1870I**

Solid and fluid vacuum cleaner, 20 l, stainless steel drum

CARATTERISTICHE TECNICHE

- single-stage by-pass motor
- voltage: 230/240 V
- frequency: 50/60 Hz
- max. power: 1200 W
- airflow rate: 58 l/sec.
- max. suction pressure: 190 mbar
- max. drum capacity: 20 l, made of stainless steel
- acoustic emissions: <70 dB(A)
- cable length: 5 m

STANDARD ACCESSORIES Ø 36 mm

- 1 corrugated hose with ergonomic handle and vent
- 2 hard extension tubes
- 1 multiuse brush for floors and fluids
- 1 flat nozzle
- 1 paper bag



NEW



FILTERING SYSTEMS

- 1 surface air filter cartridge 1900 cm² - 12 µm nom.
- 1 anti-foam filter PPI 45/PPI 30

1833...

High-brightness LED torch,
made of sturdy anodized aluminium

- adjustable focus
- 2 brightness settings



Battery life 10.0 h - L 150 mm

018330002 **1833 S**



Battery life 7.5 h - L 162 mm

018330003 **1833 M**



Battery life 8.5 h - L 196 mm

018330004 **1833 L**



Battery life 22 h - L 300 mm

018330005 **1833 XL**



L 370 mm

018380221 **1838SLIM**

Rechargeable, articulated slim 3-LED inspection lamp

- Magnetic base
- Charging time: 2.5h
- Battery life: 2-4h/ spot 3h

Triple light emission


- front: 100/200 lumens
- back: 180 lumens
- spot (head): 80 lumens



018380400 **1838AM**

Rechargeable LED inspection lamp, with double light emission, articulated, can be rotated 180°, with swivel magnetic base and hook

- double light emission: front: LED COB, 60-700 lumens, can be adjusted with potentiometer spot (head): LED SMD, 120 lumens, ON-OFF switch
- rechargeable 3.6V 2600mAh Li-ion battery
- with USB-C port
- supplied with 100-240V / 50-60Hz charger
- charging time: 4h
- battery life: front: 2.5-16h spot (head): 10h
- 3-LED battery level indicator
- articulated, can be rotated 180° (± 90° compared to axis)
- magnetic base (with neodymium magnet), can be rotated 90°
- swivel base hook



L 405 mm



018380300 **1838FLASH**

Rechargeable, ultracompact spotlight, designed to offer the best possible solution for each use

- IP65 - without external power supply
- Dual brightness: 650 / 300 lumens
- Lithium polymer battery 7.4 V 4000 mAh



018380122 **1838S**

Rechargeable, articulated LED inspection lamp


- can be rotated 180°
- nonslip rubber body
- double swinging hook
- magnets on base and back for increased adjustability
- complete with charger (100-240V / 50-60Hz)
- charging time: 4h
- battery life: 2-7.5 h



018380010 **1838COB**

Compact rechargeable inspection lamp with ultra-brightness LED. Lithium polymer battery

- Compact body made of antislip rubber
- Swinging hook
- Magnetic base can be rotated 180 degrees
- With charger 100-240Vac / 50-60Hz
- 100/200 lumens - spot 75 lumens
- Operating range: 5 / 2.5 hours
- IP65



120x59x25 mm

018360050 **1836A**

LED headlamp, dual brightness, with contactless ON/OFF sensor

- 120/65 lumens
- IP54
- Batteries: 3xAAA included



67x48x46 mm

14/7 h

1837C



Rechargeable LED spotlight for building yards

- 3 brightness settings
- battery charger: input: 100-240V AC - 50/60Hz; output: 15V 1.5A
- charging time: 4 hours
- 3-LED charge indicator
- can rotate up to 180°
- IP65
- IK07



500/1000/2100 lumen

018370210 **1837C/2100**



220x225x70 mm

1100/2200/4300 lumen

018370430 **1837C/4300**



266x236,6x59 mm

018380111 **1838/11LED**

Rechargeable inspection lamp with ultra-high brightness LEDs, lithium polymer battery

- Compact body made of antislip rubber
- With charging station, 110-230Vac
- With multidirectional head LED



EVEN MORE
COMPACT
AND BRIGHTER



WITH HEAD LED



<20%



SWINGING
HOOK



018380270 **1838E**

Rechargeable under bonnet LED lamp

- Triple light emission: 500/1000/2000 lumens
- Can be rotated 360°
- Length range: 116 ÷ 188 cm
- Aluminium body
- Nonslip rubber hooks
- USB-C charge
- Supplied with battery charger
- Input: 100-240V ~ 50/60Hz
- Output: DC 5V - 2000 mA
- battery life: 3-9 h



- 2 charging modes:**
- charge via lamp USB port
 - charge via internal battery USB port

018380271 **1838E-BT**

Rechargeable battery with USB-C port for under bonnet lamp item 1838E

- Li-Ion 3,6V
- DC 5V - 2000 mA



018370450 **1837M**



Rechargeable LED COLOUR MATCH spotlight, for visual colour control, high colour rendering index (CRI 96+), up to 2,000 lumens

- 3 brightness settings: 500/1,000/2,000 lumens
- CRI (colour rendering index): 96+
- CCT (correlated colour temperature): 2700K/ 3500K/ 4500K/ 5500K/ 6500K
- battery charger: input: 100-240V AC - 50/60Hz; output: 15V 1.5A
- quick release charge connector
- charging time: 3.5 hours
- battery life: 8/4/2 h
- charge indicator
- button and LED colour temperature indicator
- button and LED brightness indicator
- can rotate up to 180°
- IP65
- IK07



96 CRI+



220x225x70 mm

NEW THE NEW RANGE OF REELS



Beta's new, varied, comprehensive range of reels has been designed and developed with a view to satisfying all professionals' requirements.

High-resistance spring ensuring remarkable durability and unparalleled smoothness.

Drums made of thick polypropylene, for unique shock resistance.

Rack device causing automatic cable rewind to stop, easy to disable, to allow continuous pulling.

Each reel is fitted with a 180° swivel wall-mount bracket and an additional bracket for quick connection to, and disconnection from, the wall-mount support.



- length of cable out of drum: 1 m
- rack mechanism can be disabled to keep cable pulled
- coiled cable length: 15 m



018420821 **1842 15-H05/LED**

Automatic cable reel with LED inspection lamp, 100-240Vac

- with 230/12V safety transformer
- H05VV-F 2x1.0 mm² cable



018440315 **1844 15-H05**

Automatic cable reel, with 3Gx1.5 mm² cable

- 3Gx1.5 mm² cable
- with thermal protection switch
- max. power (rolled up): 1500W (230V-20°C)
- max. power (unrolled): 2500W (230V-20°C)



018440316 **1844 15-H05/SCK**

Automatic cable reel, with 3Gx1.5 mm² cable and SCHUKO type socket

- 3Gx1.5 mm² cable
- with thermal protection switch
- max. power (rolled up): 1500W (230V-20°C)
- max. power (unrolled): 2500W (230V-20°C)


1000 V

012730851 **1273MQ/D6**

Set of 6 screwdrivers

1274MQ 3x100-4x100-5,5x125 mm

1272MQ PH0x60-PH1x80-PH2x100 mm



EN 60900



012730606 **1273MQF/D6**

Set of 6 slim screwdrivers

1274MQ/F 0.5x3,5x100 - 0.8x4,5x100 -
1x5,5x125 - 1.2x6,5x150 mm

1272MQ/F PH1x4.5x80- PH2x6x100 mm



EN 60900



011690143 **1169MQ/D2**

Assortment of insulated combination pliers and insulated diagonal cutting nippers





1082MQ 160 mm



1150MQ 180 mm



EN 60900



009140054 **914MQ-A/S4**

Set of hexagon hand sockets, 3/8" female drive

made from special polyamide-based technopolymers



EN 60900

mm	Max (Nm)
8	6
10	9
13	20
17	30



For use with torque wrench

011280101 **1128MQ**

IEC 60900



Electrician's scissors, stainless steel blades, with microteeth



017600025 **1760/OHM** 

**Multimeter/megohmmeter
for high voltage insulation testing
TRUE RMS indicator**



 CAT. IV 600V
CAT. III 1000V


AC/DC voltage:	Measuring range	Base accuracy
AC/DC current:	50mV - 1000V	±0.06% - ±0.1% rdg
Resistance:	0.01μA - 10A	±0.5% - ±1% rdg
Meg OHM:	0.01Ω - 50MΩ	±0.2% - ±2% rdg
Capacity:	0.01 - 5000MΩ	±4% rdg. max current 1mA
Frequency:	5nF - 10mF	±1.5% - ±3% rdg
Temperature:	50Hz - 100 MHz	±0.02% - ±0.1% rdg
Diode test:	-50 °C - +1350 °C	±0.5% rdg
Continuity test:	3V dc	
	<30 Ω	

059880400 **5988VHB-MQ/A**

**Assortment of 66 insulated tools, 1000V,
in soft foam trays**



Quantity/Description	Beta N.	TR
12 single open end wrenches, 1000V 7-8-10-11-12-13-14-15-16-17-19-22 mm	52MQ	M49
12 single ring wrenches 7-8-10-11-12-13-14-15-16-17-19-22 mm	89MQ	M49
4 socket drivers for hexagon screws 4-5-6-8 mm	910MQ/PE	M108
11 bi-hex sockets 7-8-10-11-12-13-14-15-16-17-19 mm	910MQ/B	M108
6 socket drivers for Torx® head screws T15-T20-T25-T27-T30-T40	910MQ/TX	M108
2 socket drivers with XZN® profile 8-10 mm	910MQ/XZN	M108
1 3/8" drive extension 125 mm	910MQ/21	M108
1 3/8" drive extension 250 mm	910MQ/22	M108
1 3/8" drive, T-handle	910MQ/T	M108
1 3/8" drive reversible ratchet	910MQ/55	M108
1 electrician's scissors	1128MQ	M161
1 slip joint pliers, boxed joint 250 mm	1048MQ	M161
1 diagonal cutting nippers 1000V 160 mm	1082MQ	M161
1 combination pliers 1000V 180 mm	1150MQ	M161
1 extra long flat nose pliers 160 mm	1162MQ	M161
1 extra-long bent flat nose pliers 160 mm	1164MQ	M161
4 screwdrivers for cross head Phillips® screws, 1000V PH0x60 - PH1x80 - PH2x100 - PH3x150 mm	1272MQ	M161
4 screwdrivers for headless slotted screws, 1000V 2,5x75 - 3x100 - 4x100 - 5,5x125 mm	1274MQ	M161
1 cable stripping knife, insulated	1777MQ/U	M161



021150332 **2115PL-MQ32**

**Assortment of 32 insulated tools
for hybrid cars,
in plastic tool box with soft
thermoformed tray**



△ 1000 V

Quantity/Description	Beta N.
1 1/2" reversible ratchet	920MQ/55A
1 single ring wrenches 10-12 mm	89MQ
1 magnetic bit holder, insulated 1/4"	850MQ
10 set of 10 bits with magnetic bit holder T7-T8-T9-T10-T15-T20-T25-T27-T30-T40	860TX/A10
7 hexagon sockets 8-10-12-13-14-17-19 mm	920MQ/A
1 1/2" square drive extension bar 125mm	920MQ/21
1 1/2" square drive extension bar 250mm	920MQ/22
1 slip joint pliers, boxed joint 250mm	1048MQ 250
1 combination pliers 1000V 180mm	1150MQ
1 extra-long bent flat nose pliers 160mm	1164MQ 160
2 screwdrivers for cross head Phillips® screws, 1000V 4.5X80-6X100mm	1272MQ
3 screwdrivers for headless slotted screws, 1000V 3X100-4X100-5.5X125	1274MQ
1 insulating gloves, made from latex G2	1995MQ/G2
1 tool box, long series, made from plastic	CP15L

020010154 **2001/BZ24 MQ**

**Folding tool case with assortment
of 24 tools, for electricians**



Quantity/Description	Beta N.
1 electrician's scissors, straight blades	1128BMX
1 combination pliers 1000V 180 mm	1150MQ
5 combination wrenches 8-10-13-17-19 mm	42NEW
3 screwdrivers for headless slotted screws, 1000V 3x100 - 4x100 - 5,5x125 mm	1274MQ
3 screwdrivers for cross head Phillips® screws, 1000V PH0x60 - PH1x80 - PH2x100 mm	1272MQ
9 ball head offset hexagon key wrenches burnished 1,5-2-2,5-3-4-5-6-8-10 mm	96BP/SC9
1 mains testing screwdriver	1253
1 diagonal cutting nippers 1000V 160 mm	1082MQ

A NEW PERSPECTIVE

To redesign our electrician's scissors, we observed users' daily work. We have made it into a universal tool, incorporating the 4 main features into one object.

Cutting

Quick and sharp, for cables up to 50 mm². With a cable cutting groove and a microtoothed blade, for improved hold.

Crimping

Safe and durable, for tube terminals.

Stripping

The sensitive anti-loosening pin allows even the thinnest cables to be accurately stripped.

Countersinking

The unique milling profile allows the holes in pull boxes to be countersunk accurately and neatly.



011280095 **1128FXS**

Electrician's scissors with graduated milling profiles, straight stainless steel blades, with microteeth, cable cutting groove and crimping pliers for tube terminals

- Articulated belt hook case
- Bimaterial handles
- Anti-loose pin
- Profile and mill: designed to enlarge holes on plastic, from 13 to 21 mm



011280088 **1128BAX**

Double-acting electricians' scissors, with milling profiles in DLC-coated stainless steel

- High blade surface hardness (resistance to abrasion and wear)
- Low coefficient of friction (smoothness and anti-adherence)
- With articulated plastic case

profile and mill: designed to enlarge holes on plastic, from 13 to 25 mm.




**+HARDNESS
-COEFFICIENT
OF FRICTION**



017260050 **1726BM**

Hacksaw frame with quick release blade attachment system



017780088 **1778P**

Foldaway knife, stainless steel and aluminium blade and handle, with push button opening mechanism in case



017780080 **1778SOS**

Car service knife with window breaking hammer and seat belt cutter features, in case

- With clip and fabric wallet with loop
- Anodized aluminium handle
- Safety blade lock



017710050 **1771BM**

Utility knife, 18 mm, 6 spare blades

- Nonslip bi-material handle
- Automatic blade loading
- Blade locking nut for maximum blade stability under stress conditions
- Nonreturn safety slider



017720040 **1772M**

Safety utility knife with retractable blade, supplied with 3 blades

- Blade retracts through an automatic spring mechanism
- Die-cast alloy body
- Staple remover built into handle



**ADJUSTABLE CUTTING
DEPTH Ø÷25 MM**

The new Beta Abrasives product family is the name for a comprehensive range of hard and flexible abrasives and an outstanding technical service for professionals, as the result of the manufacturing skills contributed by the market leading companies, AbraBeta and Elpa.

// 11001

Abrasive steel and stainless steel cutting discs, with depressed centre

A30S




Ø mm	S mm	F mm		
230	3,2	22,23	110010233	

// 11035-11038 TOP LINE

Abrasive steel and stainless steel cutting discs, thin, with flat centre

A46U



	Ø mm	S mm	F mm		
11035	125	1,0	22,23	110350022	
11035	125	1,6	22,23	110350062	
11038	230	2,0	22,23	110380022	

// 11049 PREMIUM LINE

Abrasive steel and stainless steel cutting discs, thin, with flat centre

A36Q




Ø mm	S mm	F mm		
230	2,0	22,23	110490019	

// 11011

Abrasive steel grinding discs with depressed centre

A24N



Ø mm	S mm	F mm		
230	6,5	22,23	110110230	

// 11046 PREMIUM LINE

Abrasive steel and stainless steel cutting discs, thin, with flat centre


A46Q



Ø mm	S mm	F mm		
125	1,0	22,23	110460010	
125	1,6	22,23	110460016	

// 11210B PREMIUM LINE

Abrasive steel and stainless steel cutting discs, thin, with flat centre



Ø mm	P	F mm		
125	40	22,23	112100104	
125	60	22,23	112100106	
125	80	22,23	112100108	

// 11220B TOP LINE

Flap discs with zirconia abrasive cloth, fibreglass backing pad, single flap construction, cone-shaped



Ø mm	P	F mm		
125	40	22,23	112200104	
125	60	22,23	112200106	
125	80	22,23	112200108	

THE NEW RANGE OF BETA-BRANDED ANGLE GRINDERS

Power, Reliability and Durability are the three hallmarks of the new range, with the focus also being on maximum safety and ease of use for professionals.

- **Outstanding performance:**

Powerful, resin-bonded, wear-resistant, durable motor
Air vents providing optimal cooling, protected against dust infiltration

- **Unparalleled safety for operators:**

Spindle lock device for quick disc changes
Protection against accidental activation
Smooth start, for limiting large initial inrush of current on start-up

- **Unique comfort and ease of handling:**

Nonslip ergonomic handle for improved grip
Lowered head that allows working in confined spaces
Tangle-free cable no less than 4 metres in length for increased ease of movement
Additional handle that can be mounted on both sides

Available for discs 115/125/230 mm in diameter, rated absorbed power ranging from 750 W to 2,400 W.

- Protection against accidental activation
- Additional handle that can be mounted on both sides
- Tool-less disc cover (quick release)
- Spindle lock device for quick disc changes
- Lock-on/off slide switch
- Air vents protected against dust infiltration and providing optimal cooling performance
- Service wrench included

NEW

019560011 1956 115-750W **750W**

Angle grinder for discs Ø 115 mm

Ideal for cutting, grinding and roughing jobs

Powerful motor (750 W)

Nonslip ergonomic handle for increased comfort and safety
Lowered head that allows working in confined spaces
Extremely lightweight (**weighs no more than 1.8 kg**)

- Tool-less disc cover (quick release)
- Additional handle that can be mounted on both sides



Technical data

- Absorbed power: 750 W
- Voltage: 220-240 V / 50 Hz
- Disc diameter (disc not included): 115 mm
- Free speed: 11,000 rpm
- Tool spindle thread: M14
- Tangle-free cable length: 4 m
- Weight: 1.8 kg

019560125 1956 125-1400W **1400W**

Angle grinder for discs Ø 125 mm

Ideal for cutting, grinding and roughing jobs

Powerful motor (1400 W) - Variable speed

Nonslip ergonomic handle for increased comfort and safety
Lowered head that allows working in confined spaces

- Tool-less disc cover (quick release)
- Additional **anti-vibration** handle that can be mounted on both sides

Variable speed!



Technical data

- Absorbed power: 1400 W
- Voltage: 220-240 V / 50 Hz
- Disc diameter (not included): 125/115 mm
- Free speed: 3,000 - 10,000 rpm
- Tool spindle thread: M14
- Tangle-free cable length: 4 m
- Weight: 2.5 kg

019560230 1956 230-2400W **2400W**

Angle grinder for discs Ø 230 mm

Ideal for complex shearing, grinding and filing jobs

Powerful motor (2400 W)

Nonslip ergonomic handle for increased comfort and safety

- **SOFT-START FUNCTION** for a smooth start and limiting large initial inrush of current on start-up
- **ANTI-VIBRATION**
- Spindle lock device for quick disc changes



Technical data

- Absorbed power: 2400 W
- Voltage: 220-240 V / 50 Hz
- Disc diameter (not included): 230 mm
- Free speed: 6,500 rpm
- Tool spindle thread: M14
- Tangle-free cable: 4 m
- Weight: 5.8 kg

018980004 **1898/K40** 

Eco friendly, heated manual cleaning tank

- Using the bio-active liquid included, oil and residue can be effectively removed from mechanical parts without the need for aggressive chemicals
- The bio-active liquid converts the oil and other residue into carbon dioxide and water which can be re-used again and again
- no need for specialist waste collection and disposal
- suitable for both metal and plastic parts

EQUIPMENT:

- Long bristle brush and connecting pipe
- Right-hand and left-hand operation function
- Perforated stainless steel grid
- Wheels with brakes
- Card with display operating temperature and low level alert

ACCESSORIES INCLUDED:

- 2 20-l cans of environmentally friendly liquid detergent and 2 packs of bacteria
- 2 packs of bio-active liquid



EFFECTIVE AND ENVIRONMENTALLY FRIENDLY

TECHNICAL DATA

Max. pump capacity:	10 l/min
Tank capacity:	40 l
Operating temperature:	+5°C ÷ +40°C
Weight:	50 kg (when empty)

ATTENTION

Countries where product 1898/K40 is allowed to be distributed: Austria, Belgium, France (from 2021), Hungary, Italy, Netherlands, Poland, Portugal, Spain, United Kingdom.

1895 

Ultrasonic cleaning tank with special degas function

- Ultrasonic cleaning relies on fluid heating to effectively clean spare parts and metal pieces in general (carburetors, valves etc.)
- Digital display for temperature and cleaning time selection
- Two cleaning modes: "soft" and "normal"
- For normal cleaning, just use water at a temperature of 50/60 °C
- For more accurate cleaning, add non-foaming detergent solutions specific for ultrasonic tanks
- Using the degas mode speeds up air release throughout the tank, thereby improving ultrasonic cleaning efficiency



1895 6 1895 13 1895 27

Tank capacity	6 l	13 l	27 l
Drain tap	✓	✓	✓
Power	150 Watt	300 Watt	500 Watt
Heating power	300 Watt	400 Watt	500 Watt
Temperature range	0÷80°C	0÷80°C	0÷80°C
Cleaning time range	0-99 minutes	0-99 minutes	0-99 minutes
Frequency	40 kHz	40 kHz	40 kHz
Power supply	220/230V	220/230V	220/230V
Dimensions	330x180x310 mm	350x325x320 mm	530x330x380 mm

018950060 **1895 6 l**

018950130 **1895 13 l**

018950270 **1895 27 l**

014980108 **1498/8A**

Electronic car / commercial vehicle battery charger, 12 V

- Protected against polarity reversal and short circuits
- Digital backlit display
- Pull-back fixing hook



8A



Power supply voltage	220V-240V
Frequency	50-60 Hz
Rated current (Min-Max)	2-8 Amp
Battery voltage	12V
Battery capacity	5Ah-160Ah
Degree of protection	IP65
Battery type	Wet-Gel-Dry-AGM

014980126 **1498/16A**

Electronic multipurpose battery charger, 12-24V

- Backlit graphic display
- Max. charging current: 16A, continuous
- Charging and charge maintenance
- Protected against polarity reversal and short circuits
- 9 charging steps
- Floating system
- SHOW ROOM function (13.8V - 12A)
- SUPPLY function (14V - 12A)
- Memory saving function (13.8V - 12A)
- Battery recovery function
- Clamp holder
- Reclining hook fastening
- Supplied accessories: cable with clamp, cable with eyelets



16A



TECHNICAL DATA

Power supply: 220-240V
Power: 240W
Charging current: 4-16A
Battery types: Agm - Wet - Lithium (LiFePO4)
Charging capacity: 5-360Ah
Maintenance capacity: 5-550Ah
Output voltage: 12-24V
Minimum battery voltage: 0.8V
Degree of protection: IP20

017600008 **1760DGT/2**

Digital automotive multimeter, portable, with 2-channel oscilloscope and waveform generator



KIT CONTENTS:

- multimeter tips
- 2 BNC crocodile clips for oscilloscope
- tip probe for oscilloscope (1X and 10X)
- battery charger
- nylon sheath



199 mm
40 mm
98 mm

TECHNICAL DATA

Display:	2.8" colour TFT
Resolution:	320 x 240 pixels
Power supply:	100V-240V AC, 50Hz-60Hz; DC INPUT 5V DC-2A
Battery:	2 x 2600 mAh

MULTIMETER SPECIFICATIONS

Test: Voltage, Current, Resistance, Capacity, Diodes and On-Off
Max. voltage: 600V DC
Max. current: 10A DC
Max. resistance: 40MOHM
Max. capacity: 100uF



OSCILLOSCOPE SPECIFICATIONS

Horizontal

Bandwidth: 40MHz
Sampling frequency range: 250MSa/s (single channel) - 125MSa/s (double channel)
SEC/DIV range: 5ns/div ÷ 500s/div 1,2,5 sequence

Vertical

VOLTS/DIV range: 10mV/div ÷ 10V/div at BNC input
Selectable analogue, bandwidth limit, typical: 20MHz
Low frequency response (-3db): ≤10Hz at BNC
DC Gain Accuracy: ± 3% for Normal or Medium acquisition mode, 10V/div ÷ 10 mV/div

Trigger

Type: Edge
Mode: Auto, Normal, Single
Slope: Rising, Falling, Rising, & Falling
Source: CH1, CH2

Input

Coupling: DC, AC or GND
Supported probe attenuation factors: 1X, 10X, 100X, 1000X

Arbitrary waveform generator

Waveform frequency: Sine (1Hz ÷ 25MHz), Square (1Hz ÷ 10MHz), Ramp (1Hz ÷ 5MHz), EXP (1Hz ÷ 5MHz)
Width: 2.5Vpp (50Ω) - 5Vpp (high impedance)
Output impedance: 50Ω

NEW

014970180 **1497TE**

Pliers for disconnecting electrical connectors

The extremely thin noses allow the clips to be released without damaging the connectors.

L mm	A Max mm	Ø mm
215	63	4



014970200 **1497/C23**

Assortment of 23 tools for releasing electrical connectors



440x250x70 mm

014970300 **1497/C94**

Assortment of 94 car testing connectors For use with main diagnostic tools

Assortment contents:

- 2 t-taps
- 2 potentiometers
- 2 warning lights
- 2 SRS connectors
- 2 alligator clips
- 2 acicular probes
- 2 prods
- 2 dual banana connectors
- 4 single banana connectors
- 24 flat male terminals 0.6÷6 mm
- 12 round male terminals 1.6÷3.9 mm
- 24 flat female terminals 0.6÷6 mm
- 12 round female terminals 1.6÷3.9 mm



430x390x100 mm

**COMPLETE
WITH 2 T-TAPS**

017600000 **1760PA/AC-DC**

Amperometric clamp and digital multimeter

SPECIFICATIONS

DC voltage: 0.1mV ÷ 600V
AC voltage: 0.1mV ÷ 600V
AC current: 0.01A ÷ 1000A
DC current: 0.01A ÷ 1000A
Resistance: 0.1Ω ÷ 40MΩ
Capacity: 0.001nF ÷ 40 μF
Frequency: 0.001kHz ÷ 4kHz
Temperature: -40°C ÷ 1000 °C
-40°F ÷ 1832°F



500°C

017600350 **1760/IR500**

Digital infrared thermometer with dual laser aiming system

TECHNICAL DATA

Temperature range: -50 ÷ 500 °C (-22 ÷ +932 °F)
Display resolution: 0.1 °C (0.1 °F)
Emissivity: 0.1 ÷ 1 adjustable
Accuracy: -50 °C ÷ +20 °C (+/- 3 °C);
20 ÷ 500 °C (+/-2% or 2 °C)
Optical resolution (D:S): 12:1
Auto power off: ca. 10 seconds
Operating temperature: 0 °C ÷ 50 °C
Storage temperature: -20 °C ÷ 60 °C
Power supply: 1 9V battery

014980014 **1498LT/12-24**

SUITABLE FOR USE ON CARS, COMMERCIAL VEHICLES AND TRUCKS 12-24 VOLT

Portable high-performance starter, 12-24 V, ultralightweight

The microprocessor provides
total protection against:

- polarity reversal
- short circuits
- incorrect voltage
- overloads
- underdischarge
- overcharge
- overtemperature

**UP TO 10,000A
IN 5 KG WEIGHT!**



TECHNICAL DATA

- operating voltage: 12/24V
- continuous amperage: 2000/1000 A
- maximum starting amperage: 5000/2500 A
- peak amperage: 10000/5000 A
- clamp amperage: 1000 A
- cable length: 160 cm
- cable section: 25mm²
- automatic power supply: 4 Amp
- memory saving function



cable length
160 cm



NEW

014980012 **1498LT/12**

Portable high-performance starter, ultralightweight

Operating voltage	12V
Continuous amperage	800A
Maximum pickup amperage	2000A
Peak amperage	4000A
Cable length	500 mm
Battery type	4 cells LifePo4
Memory saving function	Yes
Dimensions:	260x135x72 mm
Complete with charging power supply 12 V 1,3A	



4000A



**WEIGHS NO
MORE THAN
2.5 KG!**

014980000 **1498MN/12**

Multipurpose portable starter

- Motor vehicle starting with 12-volt battery (diesel and petrol engines up to 2,000 cc)
- Charging of tablets, mobile phones and electronic devices in general
- Multi-use LED torch



240x185x60 mm



Pickup current	600A
Battery type	5V 1A-2A
Starting output	12 Volt



014980490 **1498/24**



Portable car and commercial vehicle starter, 12-24V

- Pickup current: 4200A (12V) - 2100A (24V)
- Sealed lead acid battery, solid electrolyte (AGM) type




017600170 **1760/RSE**



Signal detector

Allows power supply of parts to be tested, including common rail electro-injectors, petrol/LPG electro-injectors, piezoelectric injectors, flow regulating solenoid valves, EGR solenoid valves and coils



Performing diagnosis of individual parts of electric system only requires probe to be brought near part being tested. In systems with electromechanical/electronic parts controlled by a control unit, this tool makes it possible to check whether:

- control unit is being supplied with power and is performing its control function

- cables connecting control unit to part is efficient
- part being tested has not being disconnected
- part has not short-circuited
- part is operating electronically



014980401 **1498TB/12-24**



Digital battery tester, 12V, and starting/charging system analyzer, 12-24V

Allows the following to be tested: battery, alternator (smart and normal) and starter, diode ripple and chassis test

- fitted with software for printing test from PC
- compact, shockproof frame
- complete with input for connecting a removable mini printer (optional accessory, Beta 1498ST/TB)



BACKLIT DISPLAY



435x320x100 mm



Applications	- 12V battery test - Alternator charge test, 12-24V - Starter test
Operating range	100-2000 CCA
Reference standards	CCA, SAE, DIN, EN, IEC, JIS
Supported batteries	PB, WET, GEL, AGM, AGM FLAT, EFB
Voltmeter	9V-36V
Cable length	1600 mm
Languages	Italian, English, French, German, Spanish, Polish, Romanian, Dutch, Swedish and Finnish
Accessories included	USB cable and software

018990010 **1899A**



DPF/FAP® system cleaning machine

Special detergents can be used to periodically clean and restore DPF and FAP® systems damaged by soot and ash deposits. Results can be checked by self-diagnosis, which allows soot mass and differential pressure in diesel particulate filter before and after treatment to be determined.

COMPATIBLE WITH ANY BRAND OF DETERGENT FOR THIS TYPE OF MACHINE.



NEW



- Supplied with:
- 1 2-m-long feed pipe
 - 1 quick coupler + hose nozzle for differential sensor hoses
 - 1 niple M18x1.5 with hose nozzle for direct connection to lambda probe
 - 1 extension hose
 - 1 DPF/FAP® spray nozzle
 - 1 magnetic pipe support
 - 1 DPF/FAP® pipe with adjustment cable gland plus niple M14/16/18 mm for connecting lambda probes
- Technical specifications:
- operating voltage: 12 V
 - power supply cord length: 3.9 m
 - tank capacity: 1 l



017670100 **1767B**

NEW

Pedal and steering wheel locking kit

The trigger adjustment mechanism ensures accurate settings when keeping the vehicle accelerated.





490x285x95 mm

014650010 **1465**



Engine efficiency tester

Allows endothermic engine compression to be tested within just a few seconds, without requiring connection to engine, taking power from vehicle battery, through a dedicated software.



TAKES JUST A FEW SECONDS TO TEST COMPRESSION!

Step 1	Calculating engine rpm
Step 2	Testing battery voltage trend during each revolution
Step 3	Displaying absorbed power and compression calculated through starter operation for each piston
Step 4	Testing battery charge and efficiency



009600510 960AD/TP2

Set of adaptors for item 960TP in plastic case

Contents:

- Dummy injectors
- Dummy glow plugs
- Spark plug adaptors
- Oil cap adaptors
- Petrol injection couplers
- Set of spare gaskets

430x310x50 mm



1464T

014640377 1464IC-RK

Universal dummy injector kit for cars, trucks, marine engines and agricultural machines

Supplied with art. 1464IC

200x110x30mm



1464T

014640300 1464CBD

Comprehensive adapter set for testing compression in petrol and diesel engines, with tester 1464T

Makes it possible to connect to engine to test petrol and diesel compression with tester 1464T

Contents:

- 8 dummy spark plugs with non-return valves
- 44 dummy glow plugs with non-return valves
- 1 adjustable universal dummy injector for cars, trucks, marine engines and agricultural machines
- 1 90° adapter, pressure release valve and connecting pipe
- space accommodating tester 1464T in case

510x410x140 mm



1464T

014640470 1464FG

Set of dummy regulators for testing diesel common rail system (for use with Beta 1464T-1464AP)

Used with the tester and suitable adapters, it makes it possible to determine whether the problem is the high pressure pump or the regulator when there is no pressure in the high pressure circuit in common rail engines. Recommended for Bosch, Delphi, Denso and Siemens pressure regulators

350x250x80 mm



1464T

014640050 1464T

Digital pressure and compression tester

SPECIFICATIONS

- 5" touch screen display
- rechargeable polymer lithium battery
- complete with 80 bar sensor (for low pressure) and USB cable



014640450 1464AP

Set for testing high pressure system in common rail diesel engines, with item 1464T

- High pressure pipe set
- Fittings
- 2,000 bar sensor



430x310x50 mm

1464T

014640500 1464APB

Set for testing high pressure system in FSI petrol engines, for use with item 1464T

Comes with 200 bar sensor and connectors



240x210x50 mm

1464T



014640550 1464PT

Set for testing turbo pressure, for use with item 1464T

Comes with sensor and connecting cable



240x210x50 mm

014640570 1464VD

Vacuum testing set for item 1464T

For measuring and storing maximum vacuum value

Supplied with:

- 800 mbar sensor
- 6 and 8 mm adaptors
- 3-m-long RJ45 cable



240x210x50 mm

TECHNICAL DATA
Vacuum test: 0÷800 mbar
Resolution: 1 mbar
Maximum value storage

014640600 1464TDI

Set for testing pump pressure in TDI engines, for use with item 1464T

Comes with connector

240x210x50 mm



014640610 1464FAP

Set for testing high pressure system in common rail diesel engines, with item 1464T

- High pressure pipe set
- Fittings
- 2,000 bar sensor

240x210x50 mm



014640620 1464ADB

Set for testing AdBlue® system pressure for item 1464T

Supplied with adaptors for use with 80-bar standard sensor supplied with item 1464T

240x210x50 mm



014640650 1464PF

Set for testing pressure in braking system, for use with item 1464T

Comes with adapters and connectors

400x280x60 mm



014640700 1464PB

Set of 9 connectors for testing fuel low pressure (for use with item 1464T)

Quick connectors to tester 1464T allow fuel low pressure in diesel and petrol engines to be quickly checked

520x440x120 mm



049000112 **CA49-G**

Multi-purpose trolley with door, empty


049000102 **CX49-G**

Multi-purpose trolley, empty

MULTI-PURPOSE TROLLEY

Can be used as a mobile workstation for diagnostic tools, laptops, testers and battery chargers

- Painted sheet metal frame: unparalleled firmness and sturdiness
 - Ergonomic handle
 - 2 fixed rear castors Ø 160 mm
 - 2 steering front castors Ø 125 mm (one with brake)



2 useful side containers



1 paper holder

052000201 **CB52-0**

Gearbox/transmission trolley with liquid recovery system

Inclined plane and drain holes allow liquids to be recovered in collection tank

CAPACITY 7 L

kg 400



- Fitted with:
- 4 swivel castors, including 2 with brakes
 - tool drawer
 - pull-out liquid collection tank; capacity: 7 l
 - 2 shelves



OIL DRAIN UNITS

- level indicator
- big diameter pan with breakwater grate; capacity: 12 l
- pneumatic tank emptying through 1.8 m pipe

018770008 **1877**

Exhausted oil drain unit, wheeled, with 90 l tank



018770080 **1877A**

Exhausted oil drain unit / vacuum cleaner, wheeled, with 90 l tank and pre-chamber

- Transparent pre-chamber: capacity 9.5 l
- 1.8-m suction pipe

Standard accessories:


- 1 hard probe, Ø 5x700 mm
- 1 flexible probe, Ø 5x700 mm
- 1 hard probe, Ø 6x600 mm
- 1 flexible probe, Ø 6x700 mm
- 1 flexible probe, Ø 7x700 mm
- 1 flexible probe, Ø 8x700 mm
- adapters for VW, BMW, CITROËN



014820110 **1482SN**

Quick coupler swivel pliers for fuel pipes, with articulated jaws

NEW



017580035 1758B-RNT

Non-return quick coupling for funnel item 1758B

For Renault 1.5 dCi engine



017580030 1758B

Non-return funnel with quick couplings

Particularly suitable for VAG cars

NON-RETURN



014940325 1494MRC 38"

Special socket for plastic oil drain plugs, for Mercedes engines

17 mm



014940330 1494MAN 38"

Special socket for plastic oil drain plugs, for Mercedes engines

17 mm



014940350 1494T/C5 38"

Set of special sockets for plastic oil drain plugs

Set contents:

- 1 socket for VAG group oil drain plugs
- 1 socket for BMW oil drain plugs
- 1 socket for PSA and Ford group oil drain plugs
- 1 socket for Mercedes oil drain plugs
- 1 "T"-handle wrench



17 mm



173x125x50 mm

017580040 1758B/K5

Kit of non-return quick coupling adapters, for funnel 1758B

Kit contents:

- 1 adapter for 1.5 dCi Renault, Dacia, Nissan engines
- 1 adapter for 1.5/1.6 dCi Renault, Dacia, Nissan engines
- 1 adapter for 3.0 BMW diesel engines
- 1 adapter for 1.5/2.0 petrol engines, VAG group
- 1 connecting adapter for funnel, with tap



014870100 1487/K2 38"

2 sockets for radiator drain plugs

17 mm



014930087 1493HK

Diesel oil filter wrench for Hyundai Kia, 15-sided



014930900 **1493C/ADB**

NEW

Socket for opening AdBlue® caps, for PSA group vehicles



3/8"



17 mm

014930910 **1493U/ADB**

Socket for opening AdBlue® drain plugs



3/8"



17 mm

009600780 **960KPC**



Reversible impulse extractor with adjustable torque for glow plugs



420x185x60 mm

- Pneumatic extractor with adjustable torque and special sockets allow jammed glow plugs to be unscrewed, thereby minimizing damage risk
- 5 1/4" impact sockets, long series, specially designed for glow plugs: 8-9-10-11-12 mm, 2 extensions and 1 articulated joint
- 4 adjustable driving torques: 10-20-30-40 Nm
- Right-hand and left-hand adjustment

017590063 **1759HD/3**

Cooling system seal testing and circuit filling tools


Make it possible to check circuit (pipes, joints, pumps, radiators) for leaks under pressure and quickly fill circuit, avoiding air bubble formation

600x500x140 mm



6-MM SECTION

NEW



019490050 **1949R**

Blow gun for cleaning radiators

The 5 holes that are perpendicular to the handle allow dirt to be removed from radiators

mm	L mm
6	600

017580050 **1758ADB-D**

Non-return funnel for AdBlue®, with straight coupling

I max
1


MAXIMUM CAPACITY 1 L

017580060 **1758ADB-45°**

Non-return funnel for AdBlue®, with 45° coupling

I max
1

MAXIMUM CAPACITY 1 L




014620235 **1462/KI**

Assortment of common rail diesel injector pullers

Allows DELPHI-BOSCH-SIEMENS-DENSO injectors to be removed

- Mechanical and hydraulic operation
- Includes one 12-t hydraulic jack
- Can be directly used on vehicle with mounted engine
- Numerous adjustment options on head make it possible to work on most engines available



530x470x140 mm



009600801 **960KC-M8/M9/M10**

Assortment of tools for removing broken or damaged glow plugs

FOR SPARK PLUGS WITH THREADS M8-M9-M10



380x290x50 mm

009600280 **960BC/C5** 12"

Set of 5 sockets for injector electric connection

Set contents:

- 1 open hexagon socket, 25 mm
- 1 open hexagon socket, 27 mm
- 1 open hexagon socket, 29 mm
- 1 open hexagon socket, 30 mm
- 1 bi-hex socket, 28 mm

22 mm



280x160x55 mm

NEW

1,9 kg

014620110 **1462/MB**

Hammer face kit for removing injectors

Kit contents:

- 1 4 kg hammer face with 400 mm rod
- 1 articulated adapter, male M10x1.5, female M22x1.5 mm
- 1 adapter, male M22x1.5, female M13x1.4 mm
- 1 adapter, male M14x1.5, female M27x1 mm
- 1 adapter, male M14x1.5, male M25x1 mm
- 1 adapter, male M14x1.5, male M27x1 mm
- 1 adapter, male M14x1.5, female M14x1.5 mm
- 1 adapter, male M14x1.5, male M20x1 mm
- 1 adapter, male M14x1.5, male M17x1 mm



500x250x80 mm

7,2 kg

009600726 **960ER**

NEW

**Slide hammer
for injector washers**

**STEPPED
DRILL BIT**



014720250 **1472B/RNLT**



NEW

**Double head socket, specially
designed for suction hose
clamps installed
on Renault engines**

9 mm



014540010 **1454P**

NEW

**Scraper for removing
packing and sealant residues**

Particularly recommended for cleaning
heads and flat surfaces to match



mm	L mm	L1 mm
3,3	210	32

014810212 **1481T/C12**

NEW

Set of fuel line plugs

3 pairs of plugs with male/female
quick couplers for closing fuel lines.



275x220x45 mm

018840010 **1884**

**Oil filler tool for manual and
automatic gearboxes and
differentials**

Complete with 12 adaptors for
direct connection

- Fitted with nonreturn valve
for leakage-free oil filling
- Delivery: 70 cc per pump shot
- Tank capacity: 7.5 l
- Maximum permissible oil
viscosity: SAE 140



018840200 **1884N/C8**

NEW

Set of 8 adapters for item 1884

Set contents:

- 1 adapter for Infiniti, 7-speed, M8x1.0
- 1 adapter for Honda, Hyundai, Kia 5x8x200 mm
- 1 adapter for Skoda M18x1.5
- 1 adapter for Mini M14x1.5
- 1 adapter for Nissan M10x1.5
- 1 adapter for Nissan Juke M12x1.25
- 1 adapter for GM M12x1.75
- 1 adapter for VAG group vehicles,
7-gear



200x145x40 mm

12 ADAPTORS

FORD	AT-101
UNIVERSAL (Bmw, Honda, Nissan...)	AT-102
VW-AUDI	AT-103
VW-AUDI-PORSCHE	AT-104
VW-AUDI-MINI COOPER	AT-105
MERCEDES	AT-106
DSG	AT-107
VW-AUDI CVT	AT-108
VOLVO	AT-109
TOYOTA-LEXUS	AT-110
SKODA	AT-111
VW Passat/Tiguan <2007	AT-112

014380260 **1438K/DSG-2**

NEW

Tool set for aligning 6- and 7-speed DSG clutches

For use with 6-speed DSG and manual-shift, 7-speed DSG (series 1 and 2) and S-tronic gearboxes.



350x370x117 mm

10 kg

014910001 **1491**

38" 12"

Adjustable oil filter wrench



Ø min: 65 mm
Ø Max: 110 mm

014380270 **1438K/PWR**

Removal/installation tool set for Powershift dual clutch transmission



440x400x85 mm

10 kg

014380305 **1438DCT/S**

Tool set for aligning Ford dry dual clutches

For clutch alignment after carrying out jobs like clutch oil seal replacement



440x400x85 mm

8 kg



014710101 **1471M/C22**

Pneumatic tool for pushing back and rotating right and left disc brake pistons with accessories

in plastic case

- Automatic jack
- Thrust: 150 kg
- Operating pressure 5÷8 bar



350x310x85 mm

014660100 **1466/C5**

Kit of 5 brake bleeding wrenches

Kit contents:

- 5 wrenches sizes 7-8-9-10-11 mm
- 1 drain hose with check valve

OIL GOES INTO BUSH



260x170x50 mm

014670080 **1467T/C6**

Set of adapter plugs for brake fluid tanks, for use with BETA items 1467LF and 1467LF/2

Set contents:

- 1 plug for Toyota vehicles
- 1 plug for Ford, Hyundai, Mazda, Mitsubishi, Nissan, Subaru vehicles
- 1 plug for Honda vehicles
- 1 plug for Mazda and Suzuki vehicles
- 1 plug for Nissan vehicles
- 1 brake bleeding adapter plug for European vehicles



350x240x85 mm



NEW

014710400 **1471T/C5**

5 slogging wrenches for truck brake calipers

Can be used with torque wrenches for tightening operations

Included sizes:

- female Torx wrenches E18, E20, E24
- ring wrenches M24, M26



275x220x60 mm

019490018 **1949GPA**

Tyre inflator

- Shockproof rubber coated body
- Metal operating lever
- Operating pressure: 0.5÷12 bar, 7÷174 psi
- Pressure release feature
- Pressure measurement feature
- Pipe length: 58 cm
- 360° hose rotation
- 1/4" air inlet



NEW

019490021 **1949DGT/2**

Digital tyre inflator

- Shockproof rubber coated body
- Metal operating lever
- Operating pressure: 0.5÷12 bar, 7÷174 psi
- 4 units of measurement, bar/psi/kpa/kgf
- Backlit LCD display
- Resolution: 0.05 bar
- Self-power off after 1.5 minutes
- Hose length: 58 cm
- 360° hose rotation
- Power supply: 2 AAA batteries
- 1/4" air inlet



009720010 **972/C10**

Removal kit for damaged wheel nuts

For use on anti-theft and conventional nuts



290x250x60 mm



NEW

009720004 **972/C4BMW**

Removal kit for anti-theft bolts with free rings, for BMW and Mini cars



516x145x66 mm



009830010 **983PM**

Abrasive brush for cleaning hubs

1/2" 1/4"




Ø1 mm	Ø2 mm
90	150

009700011 **970IVECO**

Hook socket for Iveco Daily hub nuts

For versions from year 2014

IVECO



Ø1 mm	Ø2 mm
61,5	74,8

015310107 **1531/C7**

Removal kit for hub wheel bearing inner rings



Included sizes:

- 1 pliers Ø 40÷45 mm
- 1 pliers Ø 45÷51 mm
- 1 pliers Ø 50÷55 mm
- 1 pliers Ø 55÷61 mm

390x315x96 mm



015630010 **1563/C4** 

Set of 4 ball joint removal sockets

 **22/24 mm**



For use with air hammer

Set contents:

- 1 socket M12x1.25 mm
- 1 socket M12x1.5 mm
- 1 socket M14x1.5 mm
- 1 socket M16x1.5 mm

009890015 **989B**

Combination pliers for wheel balancing weights

Functions:

- Removing adhesive weights for alloy rims
- Removing weights for iron rims
- Hammer with removable PE-HD covering for adhesive weights and iron rims
- Weight jaws for iron rims



015680001 **1568**

Pneumatic assembly tool for silicone axle shaft boots

- 8 spreader arms
- Maximum arm spreading: 145 mm

L mm	L1 mm
420	195



L1



L



015670001 **1567**

Lever for removing wishbone heads and shock absorbers from pillar

One operator can position lever effortlessly and proceed with disassembly



015510020 **1551/C20** 12" 5/16"

Kit for removing shock absorber heads

Kit contents:

- 7 hexagon sockets, sizes: 16 - 17 - 18 - 19 - 21 - 22 - 24
- 1 socket extension, length: 120 mm
- 3 slotted female bits, sizes: 8x5 - 8x6 - 11x8
- 1 female hexagon bit, size: 10 mm
- 1 male XZN® bit, size: M10
- 1 male Torx® bit, size: T50
- 4 male hexagon bits, sizes: 5- 6 - 7 - 8
- 1 bit holder extension, length: 95 mm
- 1 bit holder extension, length: 190 mm



320x245x71 mm

015520020 **1552/C9**

Kit for spreading shock absorber, wishbone and steering wheel joints apart

Working with single or double retractor head also makes it possible to work on double joints, e.g. from VAG group



195x140x40 mm

mm
13

015500010 **1550U**



Pneumatic shock absorber removal tool for cars, SUVs and commercial vehicles

- upper universal hold system
- active safety system on spring
- protective "full body" grille

Supplied with 2 lower forks for diameters 78-205 mm

TECHNICAL DATA

Maximum thrust:

2 tons (10 bars) - 1.6 tons (8 bars) - 1.2 tons (6 bars)

Spring compression stroke: 335 mm



015500018 **1550U/SS187**

Left-hand fork for item 1550U

Particularly suitable for left-hand springs, e.g. Nissan Qashqai and Renault Koleos



015500021 **1550U/M**

Vice for shock absorber removal tool item 1550U

Allows shock absorber stem to be locked



MAXIMUM THRUST 2 TONS (10 BAR)

1670 mm
810 mm
825 mm



014790150 **1479LB/C5**

Kit of 5 metal trim pin removers



215x165x50 mm

013650013 **1365/K13**

Oil pressure pump, 10 t, and bodywork accessories kit in handy trolley




900x420x180 mm

Kit contents:

- oil pressure pump and piston
- wing opening pliers
- L-shaped base
- male-to-male coupling for installing accessories

014790604 **1479L/K4**

4 wrecking bars for jobs on dashboards and delicate parts



017660510 **1766ER/VW**

Low-profile window trim removal tool

Particularly suitable for VAG group window trims with reduced grip space.



L mm	H mm
215	4



NEW

013660250 **1366B**

Hammer face for plastic dent pulling glue tabs
Hammer face weight: 500 g

L mm
440



013660205 **1366KF**



013440100 **1344A/VW**

Fixing hook removal tool for Volkswagen handles



L mm
260



017680010 **1768**

Aluminium footboard

- Maximum carrying capacity: 200 kg

**SURFACE
COATED WITH
NON-SLIP
MATERIAL**

kg 200



L mm	L1 mm	H mm
960	300	475



NEW

030090001 **3009**

Wheel lifter

Maximum lifting capacity: 550 kg

- 4 pivoting rollers
- Roller width: 200 mm
- For wheels up to 240 mm in width

IDEAL FOR:

- **LOADING DAMAGED CARS ONTO TOW TRUCKS**
- **CAR REPAIR GARAGES**
- **MOVING CARS IN SHOWROOMS**



022540101 **2254K**

Reusable seat, steering wheel and gear knob protector

Suits most car seats, steering wheels and gear knobs



2254A

Car covers, for outdoor use, water-repellent and UV-resistant

Technical specifications

- exterior finish with UV protection treatment
- soft, nonscratch interior finish
- 6 adjustment strings for making cover fit close to car
- 2 front door zips to allow access to vehicle without having to remove cover
- mirror seats
- reflecting

**THESE COVERS ARE IDEAL FOR
PROTECTING DAMAGED VEHICLES WHILE
WAITING TO BE REPAIRED**



NEW

022540002 **M**

**recommended
for compact cars**
4000X1450X1300 mm

022540000 **L**

**recommended for saloon
cars and station wagons**
5300X1450X1150mm

022540001 **XL**


recommended for SUV
4700X1450X1580mm

//3099E

Outdoor motorcycle cover, water and dust resistant

Protects paint from scratches, dust and sunlight.

- Size "M" recommended for sports and naked motorcycles and mid-size scooters
- Size "L" recommended for maxi enduro and crossover motorcycles



NEW


	Tg	A mm	B mm	C mm	D mm	E mm		
3099E/M	M	2290	990	1250	350	900	030990102	
3099E/L	L	2500	1100	1650	1100	1500	030990103	

//3099T

Indoor motorcycle cover, made from stretch fabric

Protects paint from scratches, dust and sunlight

- Size "M" recommended for sports and naked motorcycles and mid-size scooters
- Size "L" recommended for maxi enduro and crossover motorcycles
- Size "XL" recommended for super touring motorcycles



	Tg	A mm	B mm	C mm	D mm	E mm		
3099T/M	M	2050	900	1000	350	800	030990202	
3099T/L	L	2700	1100	1300	550	1100	030990203	
3099T/XL	XL	3100	1300	1400	700	1200	030990204	

STRETCH FABRIC



// 030020001 3002

Creepers and seat

- Steel frame
- PVC lining with upholstery
- Easily convertible into a creeper or a seat



030030150 3003PRO



Creeper made of shockproof plastic

Complete with:

- ergonomic head cushion
- soft back protector
- 2 178 mm double bearing castors for trouble-free use on uneven surfaces and pipes/cables
- 1 castor
- double height adjustment from the ground: 38 or 76 mm
- 2 portable LED lamps (250 lumens) with fixing magnets
- load capacity: 200 kg
- weight: 7.7 kg



DOUBLE LED LAMP WITH MAGNET



H min mm	H Max mm	L mm	L1 mm
170	230	1040	570

030030151 3003PRO/SP

Wall-mounted plastic support for creeper 3003PRO

Can be mounted to walls, bridge jacks, chests of drawers or other equipment, thereby allowing creeper to be fixed through a quick system with safety closure.



030030152 3003PRO/PM

Magnetic tool holder, round, for creeper item 3003PRO

Can be applied to wheel rims of creeper to retain small items during jobs



030290120 3029L/2T



Long, lowered hydraulic jack, 2 t

Makes it possible to work on vehicles with a reduced height from the ground and internal lifting point

- Controlled descent speed
- Quick approach pedal
- Nylon wheels

**MIN HEIGHT: 75 MM
MAX HEIGHT: 530 MM**

**MAXIMUM CAPACITY:
2 TONS**



030290020 3029/2T



Lowered hydraulic jack, 2 t, with 4 wheels

- Quick approach pedal
- Steel frame and nylon wheels
- Minimum height: 75 mm

**MIN HEIGHT: 75 MM
MAX HEIGHT: 500 MM**

**MAXIMUM CAPACITY:
2 TONS**



NEW

030330130 **3033E/3T**



Hydraulic jack, 3 t

- controlled descent speed
- nylon wheels



H min-Max mm	L mm	L1 mm
95÷515	700	370

**MAXIMUM CAPACITY:
3 TONS**



030300220 **3030H/2T**



High-lift hydraulic jack, 2 t, with 6 wheels

Makes it possible to work on vehicles that are high from the ground and have a long shock absorber travel

- Controlled descent speed
- Quick approach pedal
- Nylon wheels



H min-Max mm	L mm	L1 mm
85÷780	1010	300

**MAXIMUM CAPACITY:
2 TONS**



030300020 **3030/2T**



Lowered hydraulic car jack, 2 t with 6 wheels

- Car jack can be easily handled on uneven, irregular floors
- Dual front tilting wheels made of plastic material (PTFE)
- Pedal allows easy approach



**MAXIMUM CAPACITY:
2 TONS**

H min-Max mm	L mm	L1 mm
85÷520	860	400



030330030 **3033/3T**



Hydraulic jack, 3t long version

- Particularly suitable for use on commercial vehicles
- Maximum capacity: 3t
- Polyamide wheels
- Length: 1180 mm
- Minimum plate height: 140 mm
- Maximum plate height: 520 mm

H min-Max mm	L mm	L1 mm
140÷520	1180	370

**MAXIMUM CAPACITY:
3 TONS**



NEW

030230050 **3023**

Pit and under bridge jack with screw adjustment

MAXIMUM CARRYING CAPACITY: 400 KG



H min-Max mm	Ø mm
1350÷2030	300



3010T

Jack stands, pair



	L mm	A max	g	
3010/T2	100	15 mm	60	030100002
3010/T3	150	24 mm	165	030100003
3010/T6	200	28 mm	325	030100006
3010/T10	250	34 mm	505	030100010

	Max kg	H min mm	H Max mm	
3011/T3,5	2000	280	60	030110035
3011/T5	3000	285	165	030110050
3011/T10	6000	400	325	030110100
3011/T15	10000	471	245	030110150
3011/T20	20000	34 mm	505	030110200

3011T

Hydraulic bottle jack



030250001 **3025**



Folding hydraulic crane with dual effect pump

Maximum capacity: 1 t

- Folding frame for significantly increased compactness
- 4 loading positions: 450-650-800-1000 kg
- Controlled descent speed



3050/600

Electro-hydraulic motorcycle jack, 600 kg

Technical specifications

- Electrical, mechanical and hydraulic safety devices
- Capacity: 600 kg
- Integrated electro-hydraulic unit: 230V - 50 Hz
- Hydraulic pump
- Controlled downward speed
- Safety fuses for protection in case of cable cuts
- control push button panel
- CE-certified, TÜV-approved



198 kg

Ral 2011	Ral 7016	Ral 3000
030500201	030500202	030500203

L mm	H Min mm	H Max mm
2100	185	1110



TECHNICAL DATA

- safety factor: 4
- chain-sling identification tag
- attached certificates
- manufacturer's certificate

//8097

Lifting chain sling, 2 legs with clevis grab hooks, grade 8

// 080970022 8097 D7-2

WLL t	Ø	L m
2,12	7	2

7,1 kg

// 080970042 8097 D8-2

WLL t	Ø	L m
2,8	8	2

9,1 kg

// 080970052 8097 D10-2

WLL t	Ø	L m
4,25	10	2

14,7 kg

EN818-4



//8097SL

Lifting chain slings, 2 legs, with self-locking and clevis grab hooks, grade 8

// 080970222 8097SL D7-2

WLL t	Ø	L m
2,12	7	2

7,2 kg

// 080970242 8097SL D8-2

WLL t	Ø	L m
2,8	8	2

9,1 kg

// 080970252 8097SL D10-2

WLL t	Ø	L m
4,25	10	2

15 kg

EN818-4



//8143

Hand chain blocks

- Professional model, made of first-rate materials
- Automatic brake with double pawl system
- Swivel hook with safety latch

// 081430005 8143 0,5T

WLL t	L m
0,5	3

9,2 kg

// 081430010 8143 1T

WLL t	L m
1	3

11,7 kg

// 081430020 8143 2T

WLL t	L m
2	3

19,5 kg

EN13157



//8146 EN13157

Lever hoists

- Professional model, complies with EN13157 standard, easy to install and use.
- Automatic brake with double pawl system for optimized safety.
- Swivel hook with safety latch.

// 081460002 8146C 0,25

WLL t	L m
0,25	1,5

2,5 kg

// 081460008 8146 0,75 T

WLL t	L m
0,75	1,5

6,7 kg

// 081460015 8146 1,5 T

WLL t	L m
1,50	1,5

11,2 kg


USER-FRIENDLY, SAFE



//8135

Steel plate lifting clamps with articulated lifting eyes

- Professional model, compliant with EN13155, made from high-quality materials
- Suitable for lifting steel plates, rotating by 180°, and plate transportation in vertical position
- For plates with hardness up to 30HRC (300HB)
- Cam safety lock for easier steel sheet insertion and safe gripping
- Identification plate with serial number and batch number
- Safety factor: 3:1
- Minimum WLL is 10% of maximum WLL





TECHNICAL DATA

- Safety factor: 3
 - Serial number identification plate
- ### AVAILABLE CERTIFICATES
- Manufacturer's Certificate
 - CE Declaration of Conformity
 - Test report UNI EN10204 type 2.2
 - Technical product specifications



	max WLL t	A mm	kg	
8135 0.75 T	0,75	0-15	2	081350005
8135 1.0 T	1,0	0-20	5	081350010
8135 2.0 T	2,0	0-25	8	081350020
8135 3.0 T	3,0	0-30	15	081350032
8135 5.0 T	5,0	0-50	23	081350050

max WLL (t)	Dimensions mm						
	B	C	D	E	F	G	H
0,75	205	125	10	27	105	35	40
1,0	290	170	12	48	145	45	56
2,0	375	205	17	67	175	56	56
3,0	425	237	20	75	215	60	78
5,0	480	262	20	80	232	65	90



// 019000080 **1900S 8X10**

AUTOMATIC HOSE REEL

Shockproof plastic body, for air or water

- Braided polyurethane hose
- Device for automatically fixing hose at required length
- Rack mechanism can be disabled to keep hose pulled
- Water operating temperature range: -5 °C / +50 °C
- Supplied with a 180° swivel bracket and an additional quick connection bracket

// 019000115 **1900M 10X15**



1900S 8X10 1900M 10X15

Air inlet	GAS	1/4"	3/8"
Hose length	m	10	15
Operating pressure	bar	15	15
Ø Hose	mm	8x12	10x14
Hose material		polyurethane	polyurethane

NEW


019270030 **1927XM**

12"

Compact reversible impact wrench

- Single hammer impulse device
- Amazingly compact and powerful
- One-hand reverse button
- Three power adjustable screwing positions
- Exhaust through handle
- Balancing hook

Free speed	rpm	10.000
Impulse device		Single hammer
Max. torque	Nm	770
Bolt capacity	Cl 8.8	M22●34 mm
Bolt capacity	Cl 12.9	M18●27 mm
Air inlet	GAS	1/4"
Operating pressure	bar	6,2
Internal hose size (Ø)	mm	10
Mean air consumption	l/min	122



1,3 kg

019270129 **1927XM/K5**

Assortment of 1 compact reversible impact wrench and 5 impact sockets, in plastic case

720 17-19-21-22-24 mm

307x206x86 mm



2,8 kg


019270008 **1927P**

12"

Reversible impact wrench

- Double hammer impulse device
- Lightweight and well-balanced for enhanced ease of use
- Reversible lever
- Three power adjustable screwing positions
- Exhaust through handle
- Vibration-damping handle

Free speed	rpm	7.500
Impulse device		Double hammer
Max. torque	Nm	1750
Bolt capacity	Cl 8.8	M24●36 mm
Bolt capacity	Cl 12.9	M20●30 mm
Air inlet	GAS	1/4"
Operating pressure	bar	6,2
Internal hose size (Ø)	mm	10
Mean air consumption	l/min	290



2 kg



019270118 **1927P/K3** 12"

Reversible impact wrench, supplied with 3 impact sockets



720LC 17-19-21 mm

350x305x86 mm



4 kg


019270007 **1927CD**

12"

Reversible impact wrench

- Double hammer impulse device
- Lightweight and well-balanced for enhanced ease of use
- High torque
- Reversible lever
- Three power adjustable screwing positions
- Exhaust through handle
- Silenced

Free speed	rpm	7.000
Impulse device		Double hammer
Max. torque	Nm	1020
Bolt capacity	Cl 8.8	M22●34 mm
Bolt capacity	Cl 12.9	M18●27 mm
Air inlet	GAS	1/4"
Operating pressure	bar	6,2
Internal hose size (Ø)	mm	10
Mean air consumption	l/min	130



2,3 kg

019270107 **1927CD/K3** 12"

Assortment of 1 reversible impact wrench and 3 impact sockets

720LC 17-19-21 mm

350x305x86 mm



4 kg


019270022 **1927B**

Reversible impact wrench

- "Pin Clutch" impulse device
- Rubber handle
- Reversible lever
- Three power adjustable screwing positions
- Exhaust through handle

Free speed	rpm	7.000
Impulse device		Pin Clutch
Max. torque	Nm	705
Bolt capacity	Cl 8.8	M22●34 mm
Bolt capacity	Cl 12.9	M18●27 mm
Air inlet	GAS	1/4"
Operating pressure	bar	6,2
Internal hose size (Ø)	mm	10
Mean air consumption	l/min	133

1/2"



2,1 kg

019270122 **1927B/K5**

NEW

Reversible impact wrench, made from aluminium, supplied with 5 impact sockets, in case

1/2"



15-17-19
21-22 mm

350x305x86 mm

3,5 kg

007200525 **720ME/C8**

1/2"



8 impact socket drivers for hexagon screws

Ø 5-6-8-10-12-14-17-19 mm



270x120x45 mm

007200653 **720LC/C3**

1/2"



3 impact sockets for wheel nuts, with polymeric inserts, in plastic case



Ø 17 - 19 - 21 mm



148x132x44 mm

007200904 **720/C24**

1/2"



Set of 24 impact sockets, 1/2" female drive, in metal case



Quantity/Description

- 15 10-12-13-14-15-16-17-18
19-21-22-24-27-30-32 mm
6 13-17-19-21-22-24 mm
3 17-19-21 mm

Beta N.

- 720
720L
720LC


420x185x60 mm

019280022 **1928DA**

3/4"

Reversible impact wrench

- Double hammer impulse device
- Sturdy and compact; high torque
- Reversible lever
- Three power adjustable positions
- Exhaust through handle
- Slip-proof ergonomic handle



Free speed	rpm	5.000
Impulse device		Double hammer
Max. torque	Nm	1.695
Bolt capacity	Cl 8.8	M30●46 mm
Bolt capacity	Cl 12.9	M27●41 mm
Air inlet	GAS	3/8"
Operating pressure	bar	6,2
Internal hose size (Ø)	mm	10
Mean air consumption	l/min	210


4,3 kg


3/4"
**ULTRA COMPACT
AND POWERFUL**
1.600 Nm!
019280030 1928XM
Compact reversible impact wrench


- Double hammer impulse device
- Amazingly compact and powerful
- One-hand reverse button
- Three power adjustable screwing positions
- Exhaust through handle

2,9 kg

Free speed	rpm	4.800
Impulse device		Double hammer
Max. torque	Nm	1600
Bolt capacity	CI 8.8	M27 ● 41 mm
Bolt capacity	CI 12.9	M24 ● 36 mm
Air inlet	GAS	3/8"
Operating pressure	bar	6,2
Internal hose size (Ø)	mm	10
Mean air consumption	l/min	175


019280007 1928CD
3/4"
Reversible impact wrench

- Double hammer impulse device
- High weight/power ratio
- Reversible lever
- Three power adjustable screwing positions
- Exhaust through handle
- Silenced





Free speed	rpm	4.500
Impulse device		Double hammer
Max. torque	Nm	1.800
Bolt capacity	CI 8.8	M27 ● 41 mm
Bolt capacity	CI 12.9	M24 ● 36 mm
Air inlet	GAS	3/8"
Operating pressure	bar	6,2
Internal hose size (Ø)	mm	10
Mean air consumption	l/min	215


3,5 kg
019300032 1930PA
1"
Reversible impact wrench

- Double hammer impulse device
- Auxiliary handle
- Reversible lever
- Three power adjustable screwing/unscrewing positions
- Exhaust through handle

Free speed	rpm	3.500
Impulse device		Double hammer
Max. torque	Nm	2445
Bolt capacity	CI 8.8	M36 ● 55mm
Bolt capacity	CI 12.9	M30 ● 46mm
Air inlet	GAS	1/2"
Operating pressure	bar	6,2
Internal hose size (Ø)	mm	13
Mean air consumption	l/min	350


9,6 kg
019300030 1930LH
1"
Reversible impact wrench

- Double hammer impulse device
- 210 mm (8.3") long anvil
- New 70-degree angled handle design to relieve stress and fatigue on the operator's wrists
- Auxiliary side handle
- 3 power adjustable screwing/unscrewing positions
- Lower exhaust

**EXCELLENT
WEIGHT/POWER
RATIO**


Free speed	rpm	6.000
Impulse device		Double hammer
Max. torque	Nm	2.441
Bolt capacity	CI 8.8	M36 ● 55 mm
Bolt capacity	CI 12.9	M30 ● 46 mm
Air inlet	GAS	1/2"
Operating pressure	bar	6,2
Internal hose size (Ø)	mm	13
Mean air consumption	l/min	280

7,1 kg

REVERSIBLE AIR IMPACT RATCHETS

- Double rocking dog" impulse device
- Easy tightening: The impact mechanism system eliminates wrist twisting at end of screwing and shortens operating time
- Compact and powerful: maximum torque is significantly higher than maximum torque as achieved with a conventional ratchet
- Ergonomic rubber handle

Free speed	rpm	700
Maximum torque	Nm	68
Bolt capacity	Cl 8.8	M10●16 mm
Bolt capacity	Cl 12.9	M8●13 mm
Air inlet	GAS	1/2"
Working pressure	bar	6,2
Internal hose size (Ø)	mm	10
Mean air consumption	l/min	88

019220006 1922P1

1/4"

019220010 1922P2

3/8"

019220013 1922P3

1/2"

Free speed	rpm	600
Maximum torque	Nm	136
Bolt capacity	Cl 8.8	M12●18 mm
Bolt capacity	Cl 12.9	M10●16 mm
Air inlet	GAS	1/2"
Working pressure	bar	6,2
Internal hose size (Ø)	mm	10
Mean air consumption	l/min	113



68 Nm

164 mm

0,6 kg



136 Nm

292 mm

1,5 kg

HIGH TORQUE WITHOUT AFFECTING WRIST

019330006 1933IH

High-power die grinder

- Collect chuck, Ø 3 mm and 6 mm



800 g

Free speed	rpm	20.000
Chuck capacity	mm	3-6
Power	kW	0,75
Air inlet	GAS	1/4"
Working pressure	bar	6,2
Internal hose size (Ø)	mm	10
Mean air consumption	l/min	370

019360025 1936/5A

Angle grinder


- Extremely compact and handy
- Air governor for automatically controlling top speed
- Right-hand/left-hand auxiliary handle
- Spindle lock button
- Accessory for quickly changing discs
- Safety cap can be quickly adjusted in nine different positions through quick release
- Rear exhaust



Ø 125 mm

1,9 kg


Free speed	rpm	20.000
Chuck capacity	mm	3-6
Power	kW	0,75
Air inlet	GAS	1/4"
Working pressure	bar	6,2
Internal hose size (Ø)	mm	10
Mean air consumption	l/min	370



1937

Roto-orbital palm sander, lubrication free, made from composite material

- No lubrication required
- Extremely compact and easy to handle
- 6-hole Velcro pad
- Continuous motor speed adjustment
- Nonslip, soft material handle
- Designed for connection to suction systems with swivel fittings
- Revolving exhaust



860 g

Free speed	rpm	12.000
Power	kW	0,18
Pad size	mm	150
Spindle thread		5/16"-24
Air inlet	GAS	1/4"
Operating pressure	bar	6,2
Internal hose size (Ø)	mm	10
Mean air consumption	l/min	170

	Ø mm		
1937 2,5	2,5	019370000	
1937 5,0	5,0	019370001	

017500111 1750TA

High-pressure, self-locking 6-pin grease nozzle


Once positioned, it remains on axis and connected to nipple; it does not have to be held like common nozzles
Easy to disconnect, even when with pressurized nozzle
Thread M10x1: suitable for all types of grease guns: electric, pneumatic, manual etc.
Deformation-free up to 550 bar



019460006 1946C4.8

Automatic air suction riveter

- Professional air riveter for use with 2.4 - 3.2 - 4.0 - 4.8 mm long steel, stainless steel, aluminium and copper rivets
- Pointed cone-shaped spout
- Powerful and handy, with handle made of composite material
- Complete with safety nail container and oil gun



Material/Riveter	2,4	3,2	4	4,8
copper	✓	✓	✓	✓
aluminium	✓	✓	✓	✓
steel	✓	✓	✓	✓
stainless steel	✓	✓	✓	✓


Traction power	N	8.900
Stroke length	mm	15
Maximum rivet capacity	Ø stainless steel	4,8 mm
Air inlet	GAS	1/4"
Working pressure	bar	6,2
Internal hose size (Ø)	mm	10
Air consumption	l/cycle	2,6

1,5 kg

019420000 1942A

Air saw

- Powerful and handy
- Designed for cutting bodies, exhaust pipes and silencers, aluminium and plastic
- Complete with rubber handle, PVC exhaust pipe and air-feeding hose
- Rear exhaust



Strokes per minute		10.000
Stroke length	mm	10
Air inlet	GAS	1/4"
Operating pressure	bar	6,2
Internal hose size (Ø)	mm	8
Mean air consumption	l/min	75

550 g

019490030 1949U5

Progressive blow gun with 5 nozzles

- Hard-wearing, shockproof composite material body
- 3 steel nozzles, 100/160/320 mm, scratchproof, protective rubber tips
- 1 "Turbo" nozzle made of fibreglass-reinforced nylon with safety tip
- 1 revolving nozzle, 100 mm, made of fibreglass-reinforced nylon
- With quick fixing system



019490310 1949P/U3

Progressive mini blow gun with 3 nozzles

- Hard-wearing shockproof composite material body
- Quick nozzle fixing system
- Airflow can be adjusted through ring nut rotation
- steel nozzle, 160 mm, with scratchproof, protective rubber tip (1949U5/A)
- flat, fan-shaped nozzle, made of fibreglass-reinforced nylon (1949U5/F)
- OSHA nozzle, made of fibreglass-reinforced nylon (1949U/G)



019470060 1947G2

2-in-1 grease gun

- For continuous or non-continuous grease supply
- Die-cast aluminium head
- Ergonomic handle
- Takes 400 cc cartridges or bulk grease up to 500 cc

Hose size:	mm	54 (interior) x 276 mm
Air inlet:	GAS	1/4"
Operating pressure:	bar	3÷10



2 IN 1!

2,2 Kg

- CARBON FIBRE TOE CAP
- COMPOSITE FIBRE PENETRATION-PROOF INSOLE

EN ISO
20345
2011

// 7353Y 420 g

Mesh fabric shoe, highly breathable,
with TPU inserts
High-visibility reflective mesh upper

EU	UK	
38	5	073530038
39	6	073530039
40	6,5	073530040
41	7	073530041
42	8	073530042
43	9	073530043
44	10	073530044
45	10,5	073530045
46	11	073530046
47	12	073530047
48	13	073530048

S1P HRO SRC



// 7354N 460 g

Mesh fabric shoe,
waterproof,
with TPU inserts

EU	UK	
38	5	073540038
39	6	073540039
40	6,5	073540040
41	7	073540041
42	8	073540042
43	9	073540043
44	10	073540044
45	10,5	073540045
46	11	073540046
47	12	073540047
48	13	073540048

S3 HRO SRC



// 7352A 450 g

Mesh fabric shoe,
highly breathable,
with TPU inserts

EU	UK	
38	5	073520038
39	6	073520039
40	6,5	073520040
41	7	073520041
42	8	073520042
43	9	073520043
44	10	073520044
45	10,5	073520045
46	11	073520046
47	12	073520047
48	13	073520048

S1P HRO SRC



// 7352B 450 g

Mesh fabric shoe,
highly breathable,
with TPU inserts

EU	UK	
38	5	073520138
39	6	073520139
40	6,5	073520140
41	7	073520141
42	8	073520142
43	9	073520143
44	10	073520144
45	10,5	073520145
46	11	073520146
47	12	073520147
48	13	073520148

S1P HRO SRC



// 7352G 450 g

Mesh fabric shoe,
waterproof,
with TPU inserts



NEW

EU	UK	
38	5	073520338
39	6	073520339
40	6,5	073520340
41	7	073520341
42	8	073520342
43	9	073520343
44	10	073520344
45	10,5	073520345
46	11	073520346
47	12	073520347
48	13	073520348

S1P HRO SRC ESD



- CARBON FIBRE TOE CAP
- COMPOSITE FIBRE PENETRATION-PROOF INSOLE

// 7356G  460 g

O-Gravity shoe, ultralightweight,
made of water-repellent microfibre



EU	UK	
38	5	073560038
39	6	073560039
40	6,5	073560040
41	7	073560041
42	8	073560042
43	9	073560043
44	10	073560044
45	10,5	073560045
46	11	073560046
47	12	073560047
48	13	073560048

S3 HRO SRC

// 7356V  460 g

O-Gravity shoe, ultralightweight,
made of water-repellent microfibre



EU	UK	
38	5	073560138
39	6	073560139
40	6,5	073560140
41	7	073560141
42	8	073560142
43	9	073560143
44	10	073560144
45	10,5	073560145
46	11	073560146
47	12	073560147
48	13	073560148

S3 HRO SRC

// 7357G  480 g

O-Gravity ankle shoe, ultralightweight,
made of water-repellent microfibre



EU	UK	
38	5	073570038
39	6	073570039
40	6,5	073570040
41	7	073570041
42	8	073570042
43	9	073570043
44	10	073570044
45	10,5	073570045
46	11	073570046
47	12	073570047
48	13	073570048

S3 HRO SRC

// 7357V  480 g

O-Gravity ankle shoe, ultralightweight,
made of water-repellent microfibre



EU	UK	
38	5	073570138
39	6	073570139
40	6,5	073570140
41	7	073570141
42	8	073570142
43	9	073570143
44	10	073570144
45	10,5	073570145
46	11	073570146
47	12	073570147
48	13	073570148

S3 HRO SRC

- COMPOSITE TOE CAP
- COMPOSITE FIBRE PENETRATION PROOF INSOLE

// 7317NA

Suede shoe, perforated, with microfibre reinforcement in heel area

S1P SRC



EU	UK	
35	2,5	073170135
36	3,5	073170136
37	4,5	073170137
38	5	073170138
39	6	073170139
40	6,5	073170140
41	7	073170141
42	8	073170142
43	9	073170143
44	10	073170144
45	10,5	073170145
46	11	073170146
47	12	073170147
48	13	073170148

// 7320NA

Nubuck shoe, water-repellent, with anti-abrasion reinforcement in toe cap area

S3 SRC



EU	UK	
35	2,5	073200435
36	3,5	073200436
37	4,5	073200437
38	5	073200438
39	6	073200439
40	6,5	073200440
41	7	073200441
42	8	073200442
43	9	073200443
44	10	073200444
45	10,5	073200445
46	11	073200446
47	12	073200447
48	13	073200448

// 7321NA

Nubuck shoe, water-repellent, with quick opening system and antiabrasion reinforcement in toe cap area

S3 RS SRC



QUICK OPENING
SYSTEM

EU	UK	
35	2,5	073210435
36	3,5	073210436
37	4,5	073210437
38	5	073210438
39	6	073210439
40	6,5	073210440
41	7	073210441
42	8	073210442
43	9	073210443
44	10	073210444
45	10,5	073210445
46	11	073210446
47	12	073210447
48	13	073210448

- ALUMINIUM TOE CAP
- COMPOSITE FIBRE PENETRATION-PROOF INSOLE

//7340B

Mesh fabric shoe, highly breathable, with high-frequency PU inserts and protective toe cap reinforcement made of crust suede

EN ISO 20345 2011

S1P SRC

EU	UK	
36	3,5	073400236
37	4,5	073400237
38	5	073400238
39	6	073400239
40	6,5	073400240
41	7	073400241
42	8	073400242
43	9	073400243
44	10	073400244
45	10,5	073400245
46	11	073400246
47	12	073400247



FIT PRO NET

//7341N

Microsuede shoe, waterproof, with high-frequency PU inserts and protective toe cap reinforcement made of crust suede

EN ISO 20345 2011

S1P SRC

EU	UK	
36	3,5	073410236
37	4,5	073410237
38	5	073410238
39	6	073410239
40	6,5	073410240
41	7	073410241
42	8	073410242
43	9	073410243
44	10	073410244
45	10,5	073410245
46	11	073410246
47	12	073410247



FIT PRO NET

//7322SA

Fabric shoe, highly resistant to abrasion

S3 SRC

EU	UK	
35	2,5	073220435
36	3,5	073220436
37	4,5	073220437
38	5	073220438
39	6	073220439
40	6,5	073220440
41	7	073220441
42	8	073220442
43	9	073220443
44	10	073220444
45	10,5	073220445
46	11	073220446
47	12	073220447
48	13	073220448



//7323SA

Fabric ankle shoe, highly resistant to abrasion, with quick opening system

S3 RS SRC

EU	UK	
35	2,5	073230435
36	3,5	073230436
37	4,5	073230437
38	5	073230438
39	6	073230439
40	6,5	073230440
41	7	073230441
42	8	073230442
43	9	073230443
44	10	073230444
45	10,5	073230445
46	11	073230446
47	12	073230447
48	13	073230448



QUICK OPENING SYSTEM

NEW

- COMPOSITE TOE CAP
- COMPOSITE FIBRE PENETRATION-PROOF INSOLE



EN ISO
20345
2011

//7212FG

Suede shoe, perforated,
with anti-abrasion insert
in toe cap area

S1P SRC

EU	UK	
35	2,5	072120035
36	3,5	072120036
37	4,5	072120037
38	5	072120038
39	6	072120039
40	6,5	072120040
41	7	072120041
42	8	072120042
43	9	072120043
44	10	072120044
45	10,5	072120045
46	11	072120046
47	12	072120047
48	13	072120048



//7213FG

Suede shoe with highly breathable
mesh inserts

S1P SRC

EU	UK	
35	2,5	072130035
36	3,5	072130036
37	4,5	072130037
38	5	072130038
39	6	072130039
40	6,5	072130040
41	7	072130041
42	8	072130042
43	9	072130043
44	10	072130044
45	10,5	072130045
46	11	072130046
47	12	072130047
48	13	072130048



//7214FN

Action nubuck shoe, waterproof,
with anti-abrasion insert in toe cap area

S3 SRC

EU	UK	
35	2,5	072140035
36	3,5	072140036
37	4,5	072140037
38	5	072140038
39	6	072140039
40	6,5	072140040
41	7	072140041
42	8	072140042
43	9	072140043
44	10	072140044
45	10,5	072140045
46	11	072140046
47	12	072140047
48	13	072140048



//7218FN

Action nubuck ankle shoe,
water-repellent, with anti-abrasion
insert in toe cap area and quick
opening system

S3 RS SRC

EU	UK	
35	2,5	072180035
36	3,5	072180036
37	4,5	072180037
38	5	072180038
39	6	072180039
40	6,5	072180040
41	7	072180041
42	8	072180042
43	9	072180043
44	10	072180044
45	10,5	072180045
46	11	072180046
47	12	072180047
48	13	072180048

QUICK OPENING
SYSTEM



• COMPOSITE TOE CAP

• COMPOSITE FIBRE PENETRATION-PROOF INSOLE

//7238WR

Suede ankle shoe with nylon inserts, durable rubber outsole and quick opening system WR (water-resistant) footwear

QUICK OPENING
SYSTEM



S3 HRO RS WR SRC

EN ISO
20345
2011

EU	UK	
35	2,5	072380235
36	3,5	072380236
37	4,5	072380237
38	5	072380238
39	6	072380239
40	6,5	072380240
41	7	072380241
42	8	072380242
43	9	072380243
44	10	072380244
45	10,5	072380245
46	11	072380246
47	12	072380247
48	13	072380248

//7293HM

Greased full-grain leather shoe



EN ISO
20345
2011

S3 HRO HI SRC

EU	UK	
39	6	072930639
40	6,5	072930640
41	7	072930641
42	8	072930642
43	9	072930643
44	10	072930644
45	10,5	072930645
46	11	072930646
47	12	072930647
48	13	072930648



//7294HM

Greased full-grain leather ankle shoe



EN ISO
20345
2011

S3 HRO HI SRC

EU	UK	
39	6	072940639
40	6,5	072940640
41	7	072940641
42	8	072940642
43	9	072940643
44	10	072940644
45	10,5	072940645
46	11	072940646
47	12	072940647
48	13	072940648



//7249GK

Suede ankle shoe with nylon inserts, quick opening system and reinforcement polyurethane toe cap cover

QUICK OPENING
SYSTEM



S1P RS SRC

EU	UK	
35	2,5	072490235
36	3,5	072490236
37	4,5	072490237
38	5	072490238
39	6	072490239
40	6,5	072490240
41	7	072490241
42	8	072490242
43	9	072490243
44	10	072490244
45	10,5	072490245
46	11	072490246
47	12	072490247
48	13	072490248

//7236BK

Action Nubuck ankle shoe, waterproof, with quick opening system and reinforcement polyurethane toe cap cover

QUICK OPENING
SYSTEM



S3 RS SRC

EU	UK	
35	2,5	072360335
36	3,5	072360336
37	4,5	072360337
38	5	072360338
39	6	072360339
40	6,5	072360340
41	7	072360341
42	8	072360342
43	9	072360343
44	10	072360344
45	10,5	072360345
46	11	072360346
47	12	072360347
48	13	072360348

TREKKING

- COMPOSITE TOE CAP
- COMPOSITE FIBRE PENETRATION-PROOF INSOLE



EN ISO
20345
2011

//7221PEK

Leather ankle shoe, water-repellent, with nylon inserts, anti-abrasion reinforcement in toe cap area and quick opening system

QUICK OPENING
SYSTEM

EU	UK	
35	2,5	072210235
36	3,5	072210236
37	4,5	072210237
38	5	072210238
39	6	072210239
40	6,5	072210240
41	7	072210241
42	8	072210242
43	9	072210243
44	10	072210244
45	10,5	072210245
46	11	072210246
47	12	072210247
48	13	072210248

S3 RS SRC



//7220PEK

Leather shoe, water-repellent, with nylon inserts and anti-abrasion reinforcement in toe cap area

EU	UK	
35	2,5	072200235
36	3,5	072200236
37	4,5	072200237
38	5	072200238
39	6	072200239
40	6,5	072200240
41	7	072200241
42	8	072200242
43	9	072200243
44	10	072200244
45	10,5	072200245
46	11	072200246
47	12	072200247
48	13	072200248

S3 SRC



//7222PEK

Suede shoe, perforated, with highly breathable mesh inserts

EU	UK	
35	2,5	072220135
36	3,5	072220136
37	4,5	072220137
38	5	072220138
39	6	072220139
40	6,5	072220140
41	7	072220141
42	8	072220142
43	9	072220143
44	10	072220144
45	10,5	072220145
46	11	072220146
47	12	072220147
48	13	072220148

S1P SRC



//7225PEK

Suede shoe, perforated

EU	UK	
35	2,5	072250135
36	3,5	072250136
37	4,5	072250137
38	5	072250138
39	6	072250139
40	6,5	072250140
41	7	072250141
42	8	072250142
43	9	072250143
44	10	072250144
45	10,5	072250145
46	11	072250146
47	12	072250147
48	13	072250148

S1P SRC



NEW

- STEEL TOE CAP
- COMPOSITE FIBRE PENETRATION PROOF INSOLE

//7243CK

Leather ankle shoe, water-repellent, with quick opening system

EN ISO 20345 2011

S3 RS SRC



QUICK OPENING SYSTEM

EU	UK	
35	2,5	072431335
36	3,5	072431336
37	4,5	072431337
38	5	072431338
39	6	072431339
40	6,5	072431340
41	7	072431341
42	8	072431342
43	9	072431343
44	10	072431344
45	10,5	072431345
46	11	072431346
47	12	072431347
48	13	072431348

//7245BK

Lace-up leather ankle shoe, "welder style", water-repellent, with quick opening system and front protection with strap closure

EN ISO 20345 2011

S3 RS SRC

QUICK OPENING SYSTEM

EU	UK	
35	2,5	072451235
36	3,5	072451236
37	4,5	072451237
38	5	072451238
39	6	072451239
40	6,5	072451240
41	7	072451241
42	8	072451242
43	9	072451243
44	10	072451244
45	10,5	072451245
46	11	072451246
47	12	072451247
48	13	072451248



//7246BK

Suede shoe, perforated

EN ISO 20345 2011

S1P SRC

EU	UK	
35	2,5	072461235
36	3,5	072461236
37	4,5	072461237
38	5	072461238
39	6	072461239
40	6,5	072461240
41	7	072461241
42	8	072461242
43	9	072461243
44	10	072461244
45	10,5	072461245
46	11	072461246
47	12	072461247
48	13	072461248



//7200BKK

Full-grain leather shoe, waterproof



EN ISO 20345 2011

S3 SRC

QUICK OPENING SYSTEM



//7201BKK

Full-grain leather ankle shoe, waterproof



EN ISO 20345 2011

S3 SRC

EU	UK	
35	2,5	072010435
36	3,5	072010436
37	4,5	072010437
38	5	072010438
39	6	072010439
40	6,5	072010440
41	7	072010441
42	8	072010442
43	9	072010443
44	10	072010444
45	10,5	072010445
46	11	072010446
47	12	072010447
48	13	072010448



- Stretch fabric 90% nylon, 10% spandex, 260 g/m²
- Knee pad pockets, rear pockets and leg bottoms reinforced in polyester 600D
- Slim cut
- Tearproof crotch
- Higher waisted rear for increased back protection
- Two large front pockets, one with small pocket with horizontal zip closure
- Two rear pockets with strap closure
- Large left-leg pocket with strap closure and vertical pocket with zip closure
- Front right-leg pocket with horizontal zip closure
- Large knee pad pockets with strap closure
- Ruler pocket and hammer loop

TOP line

7650

Stretch work trousers, multipocket style

XS	076500000
S	076500001
M	076500002
L	076500003
XL	076500004
XXL	076500005
XXXL	076500006

SLIM FIT



ANTHRACITE



7650B

Stretch work trousers, multipocket style

SLIM FIT



XS	076500100
S	076500101
M	076500102
L	076500103
XL	076500104
XXL	076500105
XXXL	076500106

BLUE



NEW

- Stretch fabric 86% nylon, 14% spandex, 140 g/m²
- Knee pad pockets, rear pockets reinforced in polyester 300D
- Tearproof crotch
- Two large front pockets with zip closure

SLIM FIT

NEW

ANTHRACITE

7660G

Stretch work trousers, lightweight, multipocket

XS	076600000
S	076600001
M	076600002
L	076600003
XL	076600004
XXL	076600005
XXXL	076600006

7660B

Stretch work trousers, lightweight, multipocket

XS	076600100
S	076600101
M	076600102
L	076600103
XL	076600104
XXL	076600105
XXXL	076600106

BLUE



- Stretch fabric 86% nylon, 14% spandex, 140 g/m²
- Rear pockets reinforced in polyester 300D
- Tearproof crotch
- Two large front pockets with zip closure

SLIM FIT



7661G

Stretch work Bermuda shorts, lightweight, multipocket

XS	076610000
S	076610001
M	076610002
L	076610003
XL	076610004
XXL	076610005
XXXL	076610006

ANTHRACITE



7661B

Stretch work Bermuda shorts, lightweight, multipocket

XS	076610100
S	076610101
M	076610102
L	076610103
XL	076610104
XXL	076610105
XXXL	076610106

BLUE



NEW

///7664G

GREY



Sweatshirt, long-zipped

- 60% cotton, 40% polyester, 280 g/m²
- Stretch cuffs
- Two large waist pockets with zip closure
- Chest pocket with vertical zip closure



TOP
line

XS	076640100
S	076640101
M	076640102
L	076640103
XL	076640104
XXL	076640105
XXXL	076640106

///7664N

BLACK



XS	076640000
S	076640001
M	076640002
L	076640003
XL	076640004
XXL	076640005
XXXL	076640006

///7665N

BLACK

XS	076650000
S	076650001
M	076650002
L	076650003
XL	076650004
XXL	076650005
XXXL	076650006

Hoodie, long-zipped

60% cotton, 40% polyester, 280 g/m²

- Stretch cuffs
- Two large waist pockets with zip closure
- Chest pocket with vertical zip closure
- Fixed hood with round drawcords

TOP
line



///7665G

GREY



XS	076650100
S	076650101
M	076650102
L	076650103
XL	076650104
XXL	076650105
XXXL	076650106

//7654N

Stretch microfleece sweater, short-zipped, 180 g/m², black

95% polyester, 5% spandex

XS	076540000
S	076540001
M	076540002
L	076540003
XL	076540004
XXL	076540005
XXXL	076540006



TOP
line



//7657N

Stretch fleece sweater, long-zipped, 280 g/m², black

95% polyester, 5% spandex

XS	076570000
S	076570001
M	076570002
L	076570003
XL	076570004
XXL	076570005
XXXL	076570006



//7654B

Stretch microfleece sweater, short-zipped

- 95% polyester, 5% spandex, 180 g/m², blue
- Stretch cuffs
- Chest pocket with vertical zip closure
- Polyester inserts on chest pocket and sleeves



XS	076540100
S	076540101
M	076540102
L	076540103
XL	076540104
XXL	076540105
XXXL	076540106

TOP
line



//7657B

Stretch fleece sweater, long-zipped

- 95% polyester, 5% spandex, 280 g/m², blue
- Stretch cuffs
- Two large waist pockets with zip closure
- Chest pocket with vertical zip closure
- Two interior pockets
- Polyester inserts on chest pocket and sleeves



XS	076570100
S	076570101
M	076570102
L	076570103
XL	076570104
XXL	076570105
XXXL	076570106

NEW

//7669N

TOP line

NEW

Stretch work jacket, lightweight, multipocket style

- Fabric: 86% nylon, 14% spandex, 140 g/m², black
- Water-resistant, wind-stopping, breathable and quick drying
- Detachable sleeves



XS	076690000
S	076690001
M	076690002
L	076690003
XL	076690004
XXL	076690005
XXXL	076690006

//7659N

TOP line

Softshell jacket with detachable hood and sleeves

softshell jacket, 94% polyester, 6% spandex, 290 g/m²,

S	076590001
M	076590002
L	076590003
XL	076590004
XXL	076590005
XXXL	076590006



//7904N

Beta
EASY

Work bomber jacket, padded

made of T/C canvas, 270 g/m²,
"Oxford" inserts, black
Polyester padding, 140 g/m²

XS	079040800
S	079040801
M	079040802
L	079040803
XL	079040804
XXL	079040805
XXXL	079040806
XXXXL	079040807



//7670G

CE

NEW

Anorak jacket made of Oxford polyester 300D waterproof, PU-coated, grey

- Detachable hood with stretch drawstring adjustment
- PU-coated (resistance to water columns up to 2,000 mm - breathability 2,000 mvp)
- Outer fabric: 100% polyester
- Inner fabric: 100% polyester

S	076700001
M	076700002
L	076700003
XL	076700004
XXL	076700005
XXXL	076700006



//7673NG

CE

NEW

Sleeveless work jacket, with GRAPHENE padding, 80 g/m²

- Outer fabric: front and shoulders: softshell fabric - 96% polyester, 4% spandex
back: 100% nylon 20D
- Stretch inserts on armholes

TOP line

S	076730001
M	076730002
L	076730003
XL	076730004
XXL	076730005
XXXL	076730006



LIGHTWEIGHT 180G

7860G

Work trousers

- T/C twill, 65% polyester, 35% cotton, 180 g/m²
- Inserts and knee pads made of "Oxford" polyester/PU, 220 g/m²
- Metal zip closure
- Two deep front pockets with small tool inserts with strap closure
- Large left-leg pocket with strap closure, mobile phone pocket and badge insert
- Large rear pockets with "Oxford" reinforcement and strap closure
- Ruler pocket and hammer loop
- Knee pad pockets

XS	078600800
S	078600801
M	078600802
L	078600803
XL	078600804
XXL	078600805
XXXL	078600806
XXXXL	078600807



7861G

Work Bermuda shorts

- Inserts made of "Oxford" polyester/PU, 220 g/m²
- Metal zip closure
- Two deep front pockets with small tool inserts with strap closure
- Large left-leg pocket with strap closure, mobile phone pocket and badge insert
- Large rear pockets with "Oxford" reinforcement and strap closure
- Ruler pocket and hammer loop



XS	078610800
S	078610801
M	078610802
L	078610803
XL	078610804
XXL	078610805
XXXL	078610806
XXXXL	078610807

7869G

Work jacket

- Inserts in "Oxford" polyester/PU, 220 g/m²
- Cuffs with strap adjusters
- Front strap closure with flap-covered double tap zip
- Adjustable waist
- Chest pockets with strap closure, pen pocket and badge insert
- Two deep waist pockets with strap closure

XS	078690800
S	078690801
M	078690802
L	078690803
XL	078690804
XXL	078690805
XXXL	078690806
XXXXL	078690807



7865G

Work overalls

- Inserts and knee pads made of "Oxford" polyester/PU, 220 g/m²
- Cuffs with strap adjusters
- Front strap closure with flap-covered double tap zip
- Stretch waistband
- Chest pockets with strap closure and pen pocket
- Two deep front pockets with small tool inserts with strap closure
- Large left-side pocket with strap closure, mobile phone pocket and badge insert
- Large rear pockets with "Oxford" reinforcement and strap closure
- Ruler pocket and hammer loop
- Knee pad inserts



XS	078650800
S	078650801
M	078650802
L	078650803
XL	078650804
XXL	078650805
XXXL	078650806
XXXXL	078650807

7867G

Sleeveless work jacket

- T/C twill, 65% polyester, 35% cotton, 180 g/m²
- Chest pockets with strap closure, pen pocket and badge insert
- Large waist pockets with strap closure

XS	078670800
S	078670801
M	078670802
L	078670803
XL	078670804
XXL	078670805
XXXL	078670806
XXXXL	078670807



7863G

Work bib and brace overalls

- Inserts and knee pads made of "Oxford" polyester/PU, 220 g/m²
- Metal zip closure
- Adjustable stretch shoulder straps, with quick-release snap hooks made of plastic
- Stretch waistband
- Large chest pocket with strap closure
- Two deep front pockets with small tool inserts with strap closure
- Large left-side pocket with strap closure, mobile phone pocket and badge insert
- Large rear pockets with "Oxford" reinforcement and strap closure
- Ruler pocket and hammer loop
- Knee pad pockets

XS	078630800
S	078630801
M	078630802
L	078630803
XL	078630804
XXL	078630805
XXXL	078630806
XXXXL	078630807



EASY CANVAS 260G

//7900...

Multipocket work trousers

- T/C canvas, 65% polyester, 35% cotton; 260 g/m².
- Inserts and knee pads made from "Oxford" polyester/PU, 220 g/m².
- Metal zip front with button fly.
- Two deep expanding front pockets complete with compartments for small tools, with zips and pullers.
- Double left side pocket with strap closure.
- Expanding rear pockets with flaps and strap closure.
- Hammer loop and rule pocket.
- "Oxford" snap loop.

7900P
PETROL BLUE

7900V GREEN

7900B BLUE

7900G GREY



	GREY	BLUE	GREEN	PETROL BLUE
XS	079000800	079000700	079000500	079000600
S	079000801	079000701	079000501	079000601
M	079000802	079000702	079000502	079000602
L	079000803	079000703	079000503	079000603
XL	079000804	079000704	079000504	079000604
XXL	079000805	079000705	079000505	079000605
XXXL	079000806	079000706	079000506	079000606
XXXXL	079000807	079000707	079000507	079000607

T/C canvas, 65% polyester, 35% cotton, 260 g/m²

- Inserts and knee pads made of "Oxford" polyester/PU, 220 g/m²
- Metal zip closure
- Adjustable stretch shoulder straps, with quick-release snap hooks made of plastic
- Stretch waistband
- Large chest pocket with strap closure
- Two deep front pockets with small tool inserts with strap closure
- Large left-side pocket with strap closure, mobile phone pocket and badge insert
- Large rear pockets with "Oxford" reinforcement and strap closure
- Ruler pocket and hammer loop
- Knee pad pockets

//7903G GREY

Work overalls

XS	079030800
S	079030801
M	079030802
L	079030803
XL	079030804
XXL	079030805
XXXL	079030806
XXXXL	079030807

//7903P PETROL BLUE

Work overalls

XS	079030600
S	079030601
M	079030602
L	079030603
XL	079030604
XXL	079030605
XXXL	079030606
XXXXL	079030607



//7901G

Work Bermuda shorts

- T/C canvas, 65% polyester, 35% cotton, 260 g/m²
- Inserts made of "Oxford" polyester/PU, 220 g/m²
- Metal zip closure
- Two deep front pockets with small tool inserts with strap closure
- Large left-leg pocket with strap closure, mobile phone pocket and badge insert
- Large rear pockets with "Oxford" reinforcement and strap closure
- Ruler pocket and hammer loop

XS	079010800
S	079010801
M	079010802
L	079010803
XL	079010804
XXL	079010805
XXXL	079010806
XXXXL	079010807



EASY CANVAS 260G

//79056

Work overalls

T/C canvas, 65% polyester, 35% cotton, 260 g/m²

- Inserts and knee pads made of "Oxford" polyester/PU, 220 g/m²
- Cuffs with strap adjusters
- Front strap closure with flap-covered double tap zip
- Stretch waistband
- Chest pockets with strap closure and pen pocket
- Two deep front pockets with small tool inserts with strap closure
- Large left-side pocket with strap closure, mobile phone pocket and badge insert
- Large rear pockets with "Oxford" reinforcement and strap closure
- Ruler pocket and hammer loop
- Knee pad pockets

SIZE	CODE
XS	079050800
S	079050801
M	079050802
L	079050803
XL	079050804
XXL	079050805
XXXL	079050806
XXXXL	079050807



//7907

Multipocket sleeveless work jacket

T/C canvas, 65% polyester, 35% cotton; 270 g/m²

Inserts made from "Oxford" polyester/PU, 240 g/m².

- Front closure with zip and fabric puller.
- Lined with polyester mesh.
- Seven front pockets for small tools and pen pocket.
- Expanding left pocket with flap and strap closure.
- Expanding waist pockets with zips and pullers.
- Interior mesh pockets for documents/drawings.



//7907G GREY

GREY

PETROL BLUE

SIZE	CODE	CODE
XS	079070800	079070600
S	079070801	079070601
M	079070802	079070602
L	079070803	079070603
XL	079070804	079070604
XXL	079070805	079070605
XXXL	079070806	079070606
XXXXL	079070807	079070607



//7907P PETROL BLUE

//7909

Work jacket

T/C canvas, 65% polyester, 35% cotton; 270 g/m²

- Inserts made from "Oxford" polyester/PU, 240 g/m², on elbows, shoulders and waist pockets
- Elastic cuffs with strap adjusters and rubber ends
- Zip front with flap and strap fastening
- Right pen and mobile phone pocket with zip and puller, expanding left pocket with flap and strap closure
- Waist pockets with two large insets for small tools
- Interior mesh pockets for documents/drawings/sleeves



BLUE

//7909B



GREY

//7909G



GREEN

//7909V

GREY

BLUE

GREEN

PETROL BLUE

SIZE	CODE	CODE	CODE	CODE
XS	079090800	079090700	079090500	079090600
S	079090801	079090701	079090501	079090601
M	079090802	079090702	079090502	079090602
L	079090803	079090703	079090503	079090603
XL	079090804	079090704	079090504	079090604
XXL	079090805	079090705	079090505	079090605
XXXL	079090806	079090706	079090506	079090606
XXXXL	079090807	079090707	079090507	079090607



PETROL BLUE

//7909P

095630020 9563U

Office armchair, ergonomic



95740

Work gloves,
with stretch-elastic cuffs, reinforced thumbs
and index fingers, made from touchscreen
capable synthetic leather

M	095740202
L	095740203
XL	095740204
XXL	095740205



095930200 9593S

Smartwatch, touchscreen,
fitness tracker,
silicone strap



095930205 9593SB

Smart bracelet fitness water res.



NEW

095800100 9580S

Sunglasses "Summer" style



095490091 9549ABW

Wireless bluetooth headsets



NEW

095230050 9523T

Flask, 500 ml



NEW

 **Beta**
RSC

NEW

Ø67mm




ZOOM LENS EF-S 18-135mm

Beta

winning, together

Fabio Quartararo
MotoGP World Champion 2021



Partnership 2021

998015792



8

Beta Utensili S.p.A. | via Volta, 18 | 20845 Sovico (MB) | tel +39 039 20771
www.beta-tools.com